

Twister™ Methods



Regular Maintenance - Rubber / Luxury Vinyl Tile / Composite

Twister™ pads work effectively in regular maintenance on all common floors. A Twister™ pad and water is all that is required to remove dirt and debris from the floor.

Note! Anywhere a conventional red pad and cleaning chemicals are used it can be replaced by a Twister™ Green and water.

Note! The Twister™ Green pad is also ideal for dry, high speed polishing of the floors and can be used up to 3500 rpm (UHS).

Step 1:



In order to obtain good cleaning results and to increase the lifespan of the Twister™ pad, dry mop the floor.

Step 2:



Check the machine and fill with clean water into the solution tank. Mount a Twister™ Green pad to the velcro holder with the color side down to the floor.

Note! The choice of auto-scrubber will affect the cleaning result. However, Twister™ can be used with a standard floor machine and a wet/dry vacuum:

- Pressure: 30 lbs
- RPM: 175-350+

Step 3:



Clean the floor.

Note! Check that the water flow is ok and that the integrated vac picks up the dirty water.

Step 4:



When complete, remove the Twister™ pad from the machine and rinse the pad thoroughly. Change the Twister Pad when the colored layer has disappeared.

Note! The lifespan of the Green Twister™ pad is approx 650,000 ft².

Step 5:



Use Yellow Twister™ pad for occasional interm maintenance (for extra help removing scuffs and providing a deeper clean).