



ALLPartitions

& P A R T S ©



P: 866-255-8645

F: 866-255-8640

E: help@allpartitions.com

Phenolic - Color-Thru

1.01 Work Included- The toilet partitions shall be phenolic material with floor-to-ceiling mounting style as manufactured by Accurate Partitions Corp., Lyons, Illinois.

Furnish all labor and materials necessary for completion of work in this section as shown in the approved drawings and specified herein.

1.02 Related Work – Specified elsewhere shall include accessories and anchorage/blocking for attachment of partitions.

2.01 Doors and Pilasters – Shall be 3/4" thick solid phenolic core and decorative surface sheet on both faces.

2.02 Panels and Urinal Screens – Shall be 1/2" thick solid phenolic core and decorative surface sheet on both faces.

2.03 Material – Doors, panels, pilasters and urinal screens shall be fabricated from phenolic material comprised of multiple layers of melamine resin impregnated kraft paper, and a decorative surface sheet on both faces. All layers shall be fused together under high temperature and pressure.

2.04 Finish – All components shall be water-resistant. Rough edges shall be machine sanded with a 45 degree radius edge and black finish.

2.05 Color - Shall be selected from Accurate's full range of standard designer colors.

2.06 Door Hardware – Shall be Accurate gravity cam-action hinge that permits door to return to a preset position when not locked. Hinge, strike and keeper shall be brushed aluminum to resist corrosion and through bolted with tamper resistant barrel nuts and shoulder screws. Cam-action hinge shall allow emergency access by lifting the door from the bottom.

2.07 Mounting Hardware –Stainless steel stirrup brackets with brushed finish shall be secured to walls and pilasters with stainless steel tamper proof fasteners. Panels shall be through bolted with tamper resistant barrel nuts and shoulder screws.

2.08 Construction Design – Partitions shall be anchored to the floor and overhead structural member. The pilaster shall be secured to the floor with a 1/4" x 1" stainless steel mounting bar and overhead structural member with a 3/8" x 1" steel mounting bar. Each mounting bar shall be anchored to the building structure with 3/8" cadmium-plated studs. The mounting system at the top and bottom of the

3.01 Installation – Shall be installed in accordance to the Accurate installation instructions with partitions rigid, straight and plumb. Doors and panels shall be mounted 12" above the finished floor.

3.02 Warranty – Accurate Partitions Corp. guarantees its phenolic partitions, properly maintained, against delamination, breakage or corrosion for 10 YEARS from the date of receipt by the customer. If material is found defective during that period, the material shall be replaced free of charge. No credits or allowances shall be issued for any labor or expenses relating to the replacement of components covered under the warranty plan.

Phenolic - Color-Thru

ACCURATE Phenolic Color-Thru has surface color through and through, to help diminish damage from vandalism, and even discourage it. This is in addition to the strength, durability and low maintenance which has made regular phenolic the partition of choice. Color-Thru comes in five attractive colors and is available in all four design styles.

COLOR SELECTION



6260C
Sea Spray



4350C
Camel



5350C
Red Clay



6350C
Moss



2000
Black

Actual Colors will vary from those shown do to limitations in printing process. Please make final color selection from available color samples.



FAST TRACK: 10 WORKING DAYS.

Compartment limits apply.

Any standard color - in all four styles.

Accurate Privacy & Urinal Screens

Post-to-Ceiling



POST-TO-CEILING SCREENS

Post is 1-3/4" sq. by 10' satin finish aluminum.

Shown with optional third set of stirrup brackets.

Accurate privacy and urinal screens are easy to maintain. Available in three installation configurations, and in a selection of six materials: solid plastic, plastic laminate, phenolic-black core, phenolic-color-thru, stainless steel, and powder coated steel.

Accurate styles include post-to-ceiling, floor anchored, and wall hung screens.

Floor Anchored

FLOOR ANCHORED SCREENS

Pilaster is 6" wide. Panels are 58" high by depth required.



Wall Hung

WALL HUNG SCREENS

Available in 3 standard sizes:
12" x 42", 18" x 42",
24" x 42"

Shown with optional full height aluminum brackets.

