

Features

12 Cup Automatic Coffee Brewer

- Brews 6.8 gallons of perfect coffee per hour.
- Five separately controlled warmers.
- All stainless steel construction.
- Models available with faucet. Faucet kits available for existing models also.
- SplashGard® funnel deflects hot liquids away from the hand.
- UL listed. NSF approved.



Model RT 35

(5 warmers)

(decanters not included)

Dimensions: 21.2" H x 24" W x 18.3" D

ITEM#

PROJECT

DATE

Model

RT 35
RTF 35

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-17-TL
Product No. : 30200.1000
Dimensions:
12⁷/₁₆" H x 2¹/₂" W x 3" D



Easy Clear® ED-17-TL
Product No. : 30201.1001
Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.

Paper Filter Pack
Product No. : 20115.0000
Packed per case: 1,000
Dimensions: 4¹/₄" Base x 2³/₄" Sidewall



Easy Pour® black decanter
Product No. : 06100.0101
Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



**1GPR SS Portable Server
on an RWS1 Warmer**
1GPR Product No. : 12487.0001*
RWS1 Product No. : 12203.0010
**Also available with side handles or black decor.*



BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703
Phone
800-637-8606
217-529-6601
Fax
217-529-6644
Technical Services
800-286-6070
Internet
<http://www.bunnomatic.com>

Western Regional Office
16431 Carmenita Road,
Cerritos, California 90701
Phone
562-926-0764
Fax
562-926-0858

Canadian Office
280 Industrial Parkway South
Aurora, Ontario, L4G 3T9
Phone
905-841-2866
Fax
905-841-2775

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
RT	20835.0000	120/240	19.2	3500	4050	6.8 gal./hr.	9.4	42 lbs. (19.1 kg)	No
RTF (w/faucet)	20835.0004	120/240	19.2	3500	4050	6.8 gal./hr.	9.4	46 lbs. (20.9 kg)	No

Electrical: Model requires 3-wires plus ground service rated 120/240V (115/230, 120/208), single phase, 60 hz.

Plumbing: 20-90 psi (132-621 kPa). Machine supplied with 1/4" OD male flare fitting.

