



### DE 1200

3 Joule Output Electric Fence Energizer, Controls Up To 300 Acres Overgrown Fence, Outperforms 75 Mile Energizers, All Weather Construction For Longer Life, Peak Joule Output Under The Most Difficult Fence Conditions.

| Item # | Model   | Size    |
|--------|---------|---------|
| 76-50  | DE 1200 | 3 joule |



### DE 2400

The ENFORCER by DARE is a low impedance electric fence energizer that emits 6 Joules and can control up to 600 acres. This charger is easy to install and comes with a 110 Volt plug-in.

| Item # | Model   | Size    |
|--------|---------|---------|
| 76-51  | DE 2400 | 6 joule |



### EAC 200M-Z

200 mile range, 115-volt, 60 cycle, pulsed DC output (1-second intervals), 16-joule output at 75-ohm. Features include Storm Guard lightning protection, digital timing, fuseless design, rugged, weather resistant housing, and an indicator light that shows the fence charger is working.

| Item # | Model      | Size     |
|--------|------------|----------|
| 76-52  | EAC 200M-Z | 16 joule |



### Enforcer DE120

Low impedance electric fence energizer. Model DE120. 120 VDC. 60HZ. .6W. Controls up to 20 acres. .3 joule.

| Item # | Model | Size     |
|--------|-------|----------|
| 76-78  | DE120 | .3 joule |



### Enforcer DS40

12v solar fencer powered energizer up to 40 acres.

| Item # | Model | Size      |
|--------|-------|-----------|
| 76-74  | DS40  | .01 joule |



### Enforcer DS140

Controls up to 35 acres. Outperforms rival models rated for 20 miles Operates on 4 "D" cell or remote 6/12 wet cell battery.

| Item # | Model | Size      |
|--------|-------|-----------|
| 76-75  | DS140 | .35 joule |



### DE 400

STANDARD-DUTY - SOLID STATE LOW IMPEDANCE Brand:"DARE" 110 Volts, 60 Hz 100 ACRE COVERAGE

| Item # | Model  | Size     |
|--------|--------|----------|
| 76-71  | DE 400 | 100 acre |



### DE 80

DE80 Size: 20 square Mile Features: - Fence charger-UL-listed-5 mile: 0.05 joule output-5 mile controls: up to 1 acre.-20 mile: 0.2 joule output-20 mile controls: up to 1 to 5 acres. Options: -Available in 5 mile and 20 mile sizes. Color/Finish: - Color: Black. Specifications: -110v plug-in.

| Item # | Model | Size    |
|--------|-------|---------|
| 76-61  | DE 80 | 20 mile |



### Enforcer DE200

Low impedance electric fence energizer. Model DE200. 120 VDC. 60HZ. 1W. Controls up to 50 acres. .5 joule.

| Item # | Model | Size     |
|--------|-------|----------|
| 76-80  | DE200 | .5 joule |



### Snug Insulators SC-15

Fits standard 1.3 lb.ft & 1.25 T posts. Jumbo opposed fingers take heaviest two strand barb. Wire held 1" away from steel post with mammoth 1 3/4" flange. Fi-shock.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-22  | SC-15 | 25's |



### Snap-On 2" Extender T-Post Insulator

Fits the standard studded T-post. One molded piece-needs no hardware. Packed 25 per bag. Model SC-10.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-6   | SC-10 | 25's |



### Snap-On 5" Extender T-Post Insulator

Made for T-Posts. Extends wire 5" from face of post. Use to hold down sagging field fence. Yellow in color. Model SC-20.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-17  | SC-20 | 25's |



### Reversed T-Post Insulator Extender

Fits securely on standard studded T-posts. Extends wire 5" from post. No hardware needed. Packaged 25 per bag.

| Item # | Model     | Bag  |
|--------|-----------|------|
| 76-556 | SNUG-RT25 | 25's |

### Pin Lock Insulator for T-Posts



Fits 1.25 & 1.33 lb/ft posts. Heavy cross sections withstand the pressure of high tensile fencing. Large flange prevents 'shorts' and arcing. Molded of high density polyethylene with carbon black for superior UV resistance. Performs in any climate. Black only. Model 2550-25.

| Item # | Model   | Bag  |
|--------|---------|------|
| 76-555 | 2550-25 | 25's |



### Snug HT Insulators

These two insulators are made for wood posts. Heavier and tougher than others. Insulator rests on 3/4" nail surface. Won't tear or crack loose. Flexible base fits round or flat sided posts. Molded of high density polyethylene with UV inhibitors for all weather durability. Offered with or without nails. The SNUG-HTN comes equipped with galvanized ring shank nails.

| Item # | Model    | Bag  |
|--------|----------|------|
| 76-113 | SNUG-HTN | 25's |



### Permatemp Staple Insulator

Made for wood posts. Designed to be used with high tensile permanent electric fence. Can be installed after wire is strung. Molded of highest quality polypropylene with carbon black for superior UV resistance. Performs in any climate. Type III galvanized staple included. Model 1710.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-19  | 1710  | 50's |



### Slant Nail Insulator

Comes with double-headed nail that prevents turning. For use on wood posts. 1 3/4" from post. Packed 25 per bag. SWP25.

| Item # | Model      | Bag  |
|--------|------------|------|
| 76-15  | SNUG SWP25 | 25's |



### Elfin w/Nail for Wood Posts

A proven insulator. Elfin 241 has twin wire holders. If one fails, use the other. A farmer gets two for one. Twin holder takes any standard fence wire. Metal wire holding clips not required. Weather-resistant black polyethylene performs in any climate. Model SC-250.

| Item # | Model  | Bag  |
|--------|--------|------|
| 76-81  | SC-250 | 25's |

### Snug-X5TP-15



For use on wood posts. Nails included. Extends 5" from post. For use with all gauges of wire. Packed 15 per bag. SNUG-X5TP-15.

| Item # | Model        | Bag  |
|--------|--------------|------|
| 76-14  | SNUG-X5TP-15 | 15's |

### Black Widow w/nail for Wood Posts



High density black linear polyethylene for sunlight resistance. Operates well in any climate, in any part of the world. 45 degree slot easily accepts any fence wire and holds it in place. Black Widow...a very good insulator! Model BW-WP-25.

| Item # | Model    | Bag  |
|--------|----------|------|
| 76-105 | BW-WP-25 | 25's |



### Western Screw Tight for T-Posts & Sucker Rods

Adjusts to fit: T-Posts, steel-small, medium & large, with or without studs. T posts, fiberglass-medium & large sizes only. Sucker rods- 3/4" diameter. U posts- small, 1 1/8" wide. Backside only. Insulator opens to attach anywhere on post. Yellow in color. Model SC-60.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-20  | SC-60 | 25's |



### Dual-Wire Insulator SC-200

For use with the dual-wire Electric Fence System. Mounts to steel T-posts or wood posts.

| Item # | Model  | Bag  |
|--------|--------|------|
| 76-31  | SC-200 | 25's |



### Pinlock Insulator 2249-25

Heavy cross sections withstand the pressure of high tensile fencing. Attached pin, locks and unlocks fence wire. Large flange prevents 'shorts' and arching. Molded of high density polyethylene with carbon black for superior UV resistance. Black in color.

| Item # | Model   | Bag  |
|--------|---------|------|
| 76-566 | 2249-25 | 25's |

### Screw-On Round Post Insulator



Fits on all posts 1/2" in diameter or smaller. Excellent for use with barbed wire. Completely arc proof. Packed 25 per bag. Model SC-40.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-21  | SC-40 | 25's |



### Porcelain Line Insulator

Produced from specially formulated electrical porcelain for superior dielectric and mechanical strength. Imported. Standard size with 10d double headed nail and poly washer. Model 16d-25.

| Item # | Model  | Bag  |
|--------|--------|------|
| 76-12  | 16d-25 | 25's |



### Woodex SWP-10

Comes with nails. 3" of insulator. 10 per pack.

| Item # | Model  | Bag  |
|--------|--------|------|
| 76-13  | SWP-10 | 10's |



### Porcelain Corner Insulator

Heavy duty porcelain corner and end post insulator. Imported. Model 2356-10.

| Item # | Model   | Bag  |
|--------|---------|------|
| 76-11  | 2356-10 | 10's |

### Polytape Insulators

For any fence tape up to 2" wide. Insulators grip tape tightly to prevent whipping and sawing. Large flange prevents 'shorts' and arcing. Heavy tape holder unlocks to aid installation. Molded of all-weather high density polyethylene. Yellow in colors.



### Wood Post Insulator for Tape. W/Nails.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-144 | 2330  | 25's |

### Tee Post Insulator for Tape. Fits 1.25 & 1.33 lb Posts.



| Item # | Model  | Bag  |
|--------|--------|------|
| 76-148 | SC-160 | 25's |

### Round Post Insulator for 1 1/2" Tape. Fits 1/4" to 9/16" Posts.



| Item # | Model   | Bag  |
|--------|---------|------|
| 76-160 | RP-2336 | 25's |

### Wood Post Insulator for Tape. Fits 1 1/2" posts.



| Item # | Model   | Bag  |
|--------|---------|------|
| 76-149 | 2338-25 | 25's |



### Small Screw-In Insulator

Small porcelain insulator with lag bolt. Use for line and corners. Packed Individually. Model 2802-25.

| Item # | Model   | Bag    |
|--------|---------|--------|
| 76-567 | 2802-25 | 1 each |



### Large Screw-In Insulator

| Item # | Model | Bag    |
|--------|-------|--------|
| 76-568 | 2799  | 1 each |



### T-Post Insulator Topper

| Item # | Model | Bag  |
|--------|-------|------|
| 76-18  | SC950 | 10's |



### Corner Insulator

Rounded corner. White polyethylene corner knob. Looks like porcelain. Weighs less. Works great. Model 1388-10.

| Item # | Model   | Bag  |
|--------|---------|------|
| 76-16  | 1388-10 | 25's |



### Corner Post Insulator

Insulator opens and latches closed for ease of fence installation. Molded of high density polyethylene with carbon black for superior UV resistance. Performs in any climate. Black only. Model BW-CP-10. 10 per bag.

| Item # | Model    | Bag  |
|--------|----------|------|
| 76-86  | BW-CP-10 | 10's |



### Double 'U' Insulator

An alternative method of tying off electric wires at end and gate posts. Made of non-conductive polyethylene with metal reinforcing strip. Packed 10 per bag. Model 500-542.

| Item # | Model   | Bag  |
|--------|---------|------|
| 76-120 | 500-542 | 10's |

### High Strain Corner & End Assembly



Performs superbly from any wood post or tree- as a corner- for straight line fencing. Consists of 3/8" diameter hi-carbon steel bracket, 1752 insulator and self-locking nut. All metal parts zinc plated. Model 451.

| Item # | Model | Bag  |
|--------|-------|------|
| 76-85  | 451   | 25's |



### Wire Stretcher

Reliable, proven design grips any type of wire to aid in splicing and stretching wire fencing. Securely holds both wire ends in place as you splice, making fence repairs easier. Wire Stretcher is ruggedly built with strong hooks and powerful, easy-to-use ratchet action.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-534 | A-53  | Fi-Shock |

### Fence Stretcher



Great for 48" to 52" field fence; chain link fence from 36" to 48"; and many others. U-channel holds wire fence firmly. Woven wire fence stretcher allows fence to be pulled evenly and tightly.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-538 | A-54  | Fi-Shock |



### 48" Electric Fence Post

Cold drawn steel electric fence posts with permanent protective coating have 2-1/2" anchor plates that are double-welded for additional strength. Posts are 11/32" round, 48" long, weigh 1.16 lbs.

| Item # | Size | Color    |
|--------|------|----------|
| 76-23  | 48"  | Burgundy |



### Step-In Poly Post

Molded clips hold electric fence wire & polytape up to 2" wide. Molded of reinforced polypropylene with a heavy-duty steel stake. Extra reinforcing ribs for strength. Features large step-in flange & anti-rotation spike- keeps stake from turning.

| Item # | Size | Box |
|--------|------|-----|
| 76-690 | 4'   | 50  |
| 76-700 | 64"  | 20  |



### Electro-Tape

This is our widest tape. Made of high visibility white polyethylene and 12 extra large .23 MM diameter stainless steel conductors.

| Item # | Size   | Length |
|--------|--------|--------|
| 76-37  | 1/2"   | 656'   |
| 76-38  | 1 1/2" | 656'   |



### Equi-Rope

1/4" x 660 ft. Ideal for horse fencing, electrified gates and other electric fencing applications. White in color.

| Item # | Size | Length |
|--------|------|--------|
| 76-750 | 1/4" | 660'   |



### Poly Wire

White polyethylene cord woven of UV resistant polyethylene with three strands of strong stainless steel wire. 400 meters. Model 3177.

| Item # | Model | Length |
|--------|-------|--------|
| 76-755 | 3177  | 1312'  |



### High Tensile Wire

12 1/2" gauge 200,000 psi steel wire with type III zinc coating. Made to last a generation or more. Rewound for easy handling with spinning jenny.

| Item # | Size  | Type         |
|--------|-------|--------------|
| 77-706 | 2000' | Regular      |
| 77-704 | 4000' | Zinc Alum.   |
| 77-703 | 4000' | Reg. Spliced |

### Gate Anchor Kit



T-Post and wood Posts. Consists of: two #2238 anchors, two #2249, nails, and two #2550 insulators. (Gate handle not included)

| Item # | Model | Type |
|--------|-------|------|
| 76-10  | 3230  | Dare |

### Bungee Gate



Bungee style gate is safe for horses and all livestock. Stretches to fit openings up to 20 feet. Hardware included for both Wood and T-Post.

| Item # | Model | Type |
|--------|-------|------|
| 76-26  | 2950  | Dare |

### Gate Slinky



Stretches to fit gate opening up to 20 feet. Retracts to keep gate off ground when open. Electrified when closed, neutral when open. Highly visible and effective. SLINKY GATE assembly consists of: One Rub'rgate handle, one large galvanized spring, two pinlock style wood post insulators with galvanized nails, two pinlock style T-Post insulators, one anchor/activator, one fence line clamp/tap and complete schematic instructions. Equipped to fit wood post or T-Post openings.

| Item # | Model | Type |
|--------|-------|------|
| 76-24  | 2222  | Dare |

### Plastic Gate Handle



Molded of tough, high quality plastic with shock-proof thickness for safe handling protection. Model A-5.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-7   | A-5   | Fi-Shock |

### Rubber Gate Handle



Virtually indestructible, won't crack in cold weather. Tough polymer liner provides extra safety and strength. Model 1247.

| Item # | Model | Type |
|--------|-------|------|
| 76-1   | 1247  | Dare |

### Old Ironside Handle



| Item # | Model | Type |
|--------|-------|------|
| 76-9   | 1793  | Dare |

### Splicing Buckle

Made for 1 1/2" tape. Model 2880.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-151 | 2880  | Fi-Shock |



### 8' Ground Rod w/Clamp

Copper-coated ground rod including heavy-duty ground clamp. Model A-7.

| Item # | Model  | Type        |
|--------|--------|-------------|
| 76-522 | A-7    | Rod w/Clamp |
| 76-521 | HT-410 | Clamp       |

### Lightning Arrestor Kit



Helps protect fence controller from damage caused by lightning. Kit contains lightning arrester, connector clamp, 8-point ground clamp and mounting screws. Model A-11

| Item # | Model | Type     |
|--------|-------|----------|
| 76-925 | A-11  | Fi-Shock |

### Electric Fence Warning Sign



Has the words "Electric Fence" printed on both sides. 4" x 8" bold black letters on bright yellow laminated vinyl. Two holes to nail on post or hang from wire. Model 1614. 3 per pack.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-25  | 1614  | Fi-Shock |

### 10" Fence Tool



| Item # | Model | Type     |
|--------|-------|----------|
| 76-509 | 3001  | Fi-Shock |

### Multi-Light Electric Fence Tester



Lights calibrated to glow from 600 to 5500 volts. Measures voltage drop between points along fence. Model A-65.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-4   | 1360  | Fi-Shock |

### Electric Fence Tester



Molded of high impact ABS. Light indicates current flow through fence wire. Model A-6.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-3   | 460   | Fi-Shock |



### Switch

For outdoor use on electric fence. Install several in each electric fence for convenience and safety. Switch off areas to allow repairs. Use to change polarity of fence wires. Single throw switch. Model 500-562.

| Item # | Model   | Type |
|--------|---------|------|
| 76-8   | 500-562 | Dare |



### 1 Amp Fuse 5-Card

This fuse is used in the majority of fence controllers requiring fuses. Packed 5 fuses per peggable card. Model 301-402.

| Item # | Model   | Type |
|--------|---------|------|
| 76-27  | 301-402 | Dare |



### 3 Prong Circuit Breaker

For use with the Fi-shock Model SS-900 weed-clipper controller. Model 301-506.

| Item # | Model   | Type     |
|--------|---------|----------|
| 76-28  | 301-506 | Fi Shock |



### 4 Prong Circuit Breaker

Four prong style to fit weed nipping type of electric fence controllers. Model 483-4.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-29  | 483-4 | Fi Shock |

### Strainer Handle



| Item # | Model | Type |
|--------|-------|------|
| 76-542 | 2776  | Dare |

### Tension Spring



Used to measure tension of wire. One inch of compression equals 150 lbs. of pull. Use one in conjunction with in-line strainer for each leg of fence. Electroplated to deter rust. Model 400-401.

| Item # | Model   | Type     |
|--------|---------|----------|
| 76-543 | 400-401 | Fi Shock |



### Dual-Wire Indicator Light

Packed 3 per blister card. Dual-wire indicator light recommendations: Battery and solar-powered energizers- Up to three lights; AC-powered energizer with open circuit output voltage of 4,600 V or greater.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-76  | A-200 | Fi Shock |



### Spinning Jenny w/Brake

Allows easy payout for coiled wire. Includes built-in brake to prevent wire from coiling up. Model 300-303.

| Item # | Model   | Type     |
|--------|---------|----------|
| 76-526 | 300-303 | Fi-Shock |

### High Tensile Wire Cutters



Specially hardened jaws to cut 12 1/2" gauge high tensile fence wire. Comfortably shaped handles lock closed to carry-spring open to use. Model 2290.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-512 | 2290  | Fi-Shock |



### 4 Slot Crimping Tool

The four slots allow a wide range of wire or cables to be spliced with one tool. 1-2 slot for 14 1/2" & 15 1/2" ga. wire. 2-3 slot for 12 1/2" ga. wire. 3-4 slot for 10 & 11 ga. wire & 14 & 15 ga. barbed wire. 4-5 slot for 9 ga. wire & 12 1/2" & 13 1/2" ga. barbed wire. Packed 1 per box. Model 300-320.

| Item # | Model | Type |
|--------|-------|------|
| 76-511 | 2154  | Dare |



### On-Line Strainer

A wire tensioning device. Wire doesn't need to be cut. Model 9400.

| Item # | Model | Type |
|--------|-------|------|
| 76-541 | 9400  | Dare |



### In-Line Strainer w/Compression Clip

Used to tighten high-tensile wire. Under compression, it automatically feeds into cog reel. Model 1703.

| Item # | Model | Type |
|--------|-------|------|
| 76-540 | 1703  | Dare |



### In-Line Strainer Handle

Made of hot rolled flat steel formed to fit the in-line strainer. Cadmium electroplated to prevent rust. Model 1701.

| Item # | Model | Type |
|--------|-------|------|
| 76-546 | 1701  | Dare |

### In-Line Strainer w/Square Head



| Item # | Model | Type     |
|--------|-------|----------|
| 76-537 |       | Fi-Shock |



### Mini Reel

Holds 825' of polywire or 330' of polytape.

| Item # | Model | Type     |
|--------|-------|----------|
| 76-42  | WW-1  | Fi Shock |



### Brace Pins

Use to hold horizontal brace beams. 3/8" dia. x 5" & 10". Galvanized steel. 5 per package.


| Item # | Model | Type |
|--------|-------|------|
| 76-544 | 1715  | 5"   |
| 76-545 | 1714  | 10"  |



### Crimping Sleeves

| Item # | Size        | Ct. | Wire Use   |
|--------|-------------|-----|------------|
| 76-527 | 3-4:        | 10  |            |
| 76-528 | 2-3: 3/8"   | 100 | 12.5 Ga    |
| 76-529 | 2-3: 11/16" | 100 | 12.5 Ga    |
| 76-530 | 3-4: 1/2"   | 100 | 10 & 11 Ga |
| 76-531 | 4-5: 1/2"   | 10  | 9 Ga       |
| 76-532 | 2-3         | 500 |            |

### Tube Style Wood Post Insulator



Rigid high density polyethylene with carbon black for superior UV resistance. Performs in any climate. Four inches long x 3/8" diameter. Ribs prevent insulator from sliding. Comes without staple.

| Item # | Model | Ct  |
|--------|-------|-----|
| 76-516 |       | 50  |
| 76-517 |       | 200 |



### 20" Wrap Around Insulator

Use for tying off electric wires at end and gate posts. Made of non-conductive polyethylene with an aluminum insert for strength. Packed 10 per bag.

| Item # | Size | Ct |
|--------|------|----|
| 76-547 | 20"  | 10 |



### 50' Insultube

Used for insulating hot feed wires to be strung overhead or underground to bring electricity to the fence. Can also be cut to insulate live wires from neutral wires, and to enclose wires buried underground for crossing underneath gateways. 50' per roll

| Item # | Model | Size |
|--------|-------|------|
| 76-551 | 2453  | 50'  |



### Fence Taps DPT

Use to splice 12 1/2 gauge smooth wire. Model DP 3-4/10. Bag of 10. One side is open J.

| Item # | Ct. | Type |
|--------|-----|------|
| 76-88  | 10  | Dare |

### Wire Twisting Tool



Use to spin, bend, splice, and dice, high tensile wire. Also used to bend T-post and batten clips. 7/16" diameter x 5" zinc plated steel tool. Drilled three holes.

| Item # | Ct. | Type |
|--------|-----|------|
| 76-510 | 1   | Dare |



### Dual Wire Separator

Packed 25 per bag. Model SC-201.

| Item # | Model  | Type     |
|--------|--------|----------|
| 76-30  | SC-201 | Fi-Shock |



### Underground Cable

Used in same manner as 500-546, except you do not have to thread the wire through the tubing. Made of non-conductive polyethylene which is extruded around 12 1/2 gauge, 170,000 PSI, Class 3 galvanized wire.

| Item # | Model | Size |
|--------|-------|------|
| 76-126 | 2488  | 50'  |
| 76-127 | 2212  | 165' |



Co-Line

### Two Way Lockable Latch

Fits all gates with round tube from 1 5/8" - 2" diameter. Latch will release to allow gate to swing either direction. One-handed operation. Prevents gate end from sagging or swinging.

| Item # | Model | Size        |
|--------|-------|-------------|
| 74-162 | 2 way | 1 5/8" - 2" |



Co-Line

### One Way Lockable Latch

Fits all gates with round tube from 1 5/8" - 2" diameter. One-handed operation. Prevents gate end from sagging or swinging.

| Item # | Model | Size        |
|--------|-------|-------------|
| 74-163 | 1 way | 1 5/8" - 2" |



Co-Line

### Sure Stop Gate Anchor

Holds gate in any open position. Prevents gate end from sagging or swinging. May also be used horizontally as a slide latch. Makes daily chores easier.

| Item # | Model | Size |
|--------|-------|------|
| 74-165 |       |      |



Co-Line

### Gate Wheel

Fits all gates with round tube from 1 5/8" - 2" diameter.

| Item # | Model | Size      |
|--------|-------|-----------|
| 74-167 |       | 1 5/8"-2" |



### Two Way Sure Latch Jr

For use on residential, commercial, or livestock gates with 1 1/4" - 1 1/2" O.D. round tube.

| Item # | Model | Size          |
|--------|-------|---------------|
| 74-164 |       | 1 1/4"-1 1/2" |



### Splicers

| Item # | Model  | Size      |
|--------|--------|-----------|
| 76-130 | PA50T  | 1/2" tape |
| 76-132 | PA100T | 2" tape   |

### Fence Staples

| Item # | Size   | Weight |
|--------|--------|--------|
| 77-133 | 1 1/4" | 10 lb  |
| 77-134 | 1 1/2" | 10 lb  |
| 77-136 | 1 3/4" | 10 lb  |
| 77-137 | 2"     | 10 lb  |
| 77-753 | 1 1/4" | 50 lb  |
| 77-754 | 1 1/2" | 40 lb  |
| 77-756 | 1 3/4" | 40 lb  |
| 77-757 | 2"     | 50 lb  |

### Acresage Table

Below are suggested guidelines. Assumes square area to be fenced. Amount of fence needed will increase as area gets narrower and longer.

| Acres | Fence<br>20 Rod<br>Rolls | Fence<br>100 ft<br>Rolls | Barb<br>Wire<br>80 Rod<br>Rolls<br>1 Strand |
|-------|--------------------------|--------------------------|---|
| 1     | 3                        | 9                        | 1   |
| 2     | 4                        | 12                       | 1   |
| 3     | 5                        | 15                       | 1   |
| 4     | 5                        | 17                       | 2   |
| 5     | 6                        | 19                       | 2   |
| 6     | 7                        | 21                       | 2   |
| 7     | 7                        | 22                       | 2   |
| 8     | 8                        | 24                       | 2   |
| 9     | 8                        | 25                       | 2   |
| 10    | 8                        | 26                       | 2   |
| 11    | 8                        | 28                       | 2   |
| 12    | 9                        | 29                       | 3   |
| 13    | 10                       | 31                       | 3   |
| 14    | 10                       | 31                       | 3   |
| 15    | 10                       | 33                       | 3   |
| 20    | 12                       | 38                       | 3   |
| 25    | 13                       | 42                       | 4   |
| 30    | 14                       | 46                       | 4   |
| 35    | 15                       | 50                       | 4   |
| 40    | 16                       | 53                       | 4   |
| 45    | 17                       | 56                       | 4   |
| 50    | 18                       | 60                       | 5   |



### Polytape Wire Tighteners

5pc polywire tightener. Use with polywire, 1/2" polytape, and steel wire gauges 9 thru 18. Not designed for high-tensile. 5 to a package.

| Item # | Model | Size |
|--------|-------|------|
| 76-40  | 2769  | 5's  |





### Post Driver

Strong pipe construction. 3/8" O.D. model. Angled handles for easier motion. Painted Applegate Red.

| Item # | Model    | Color |
|--------|----------|-------|
| 74-61  | w/Handle | Red   |



### Earth Anchors

Offered in various lengths. Welded eye for wire to easily slide through. 3" and 4" disc models have 120mm discs. 6" disc models have 180mm discs. Painted Applegate Red.

| Item # | Size     |
|--------|----------|
| 74-37  | 3" x 15" |
| 74-41  | 3" x 30" |
| 74-42  | 4" x 40" |
| 74-43  | 6" x 48" |