

Survivor® LED Flashlight

Specific lighting needs require specific tools. With the right lighting tool, you can identify potential or existing problems before they interrupt your ability to get the job done. In addition the costs savings of using the right tool over time will benefit your bottom line.

LEDs don't require periodic bulb replacement like incandescents and are virtually indestructible. Streamlight's revolutionary C4 technology combined with an innovative Streamlight-engineered reflector provides sharp, focused light that rivals incandescent intensity without giving up the durability and longevity of an LED. Since LEDs have a long life and won't burn out or won't break, they never need to be replaced. Your light will always be ready when you need it. More powerful and more economical, Streamlight rechargeable LED lighting tools pack a lot more power with ultra-bright white beams and long illumination times. They are extremely dependable and cost-efficient.

A "hands-free" working situation is much more productive, not to mention safer. No need to juggle while you work to complete a task with one hand while holding your flashlight in the other. Hands-free lighting tools are used wherever there's a need to use both hands. If you work in a hazardous environment, a safety-rated hands-free lighting tool is essential. Ensure a safer, "hands-free," more productive workplace by offering a Streamlight Survivor LED which can either stand on its own or attached to belts/harnesses/turnout gear with spring-laod clip with superior retention.

Case Material: Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance. Spring loaded clip with built in ring easily attaches to belts and harnesses. Unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy duty bezel. O-ring sealed. Available in international safety orange, high visibility yellow or black.

Dimensions: Height: 7.06 in. (17.92 cm); Height in charger: 8.67 in. (22.02 cm); Width: 2.85 in. (7.24 cm); Diameter: 2.87 in. (7.29 cm)
Grip area: Height: 3.6 in. (9.14 cm); Thickness: 1.35 in. (3.43cm); Width: 2.20 in. (5.59 cm)

Weight: NiCd: 17.9 oz (508 grams)*, Alkaline: 13.1 oz (371 grams)*

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime

Light Output: Deep-dish parabolic reflector produces narrow beam; ideal for smoke-cutting applications. Optimum peripheral illumination to aid in navigation. Sonic welded push button switch designed for extremely long life. Rubber dome push button actuator provides easy operation even when wearing heavy gloves.

On/Off: Raised push-button switch for easy use with gloves. 3-position switch: high, low, locator strobe light

Battery: Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C can be recharged up to 1,000 times. Optional four (4) "AA" alkaline battery pack provides fast replacement with readily available batteries.

Charging: One-hour fast chargers with full charge indicators designed specifically for AC or DC power sources.

Features: • IPX4 rated design; water resistant • 2 meter impact resistance tested.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction



Flash: 8 hours continuous; Moonlight: 20 days continuous		
FL STANDARD	HIGH	LOW
	140 LUMENS	47 LUMENS
	3h 30min	13h
	379m	219m
	36,000cd	12,000cd

Flash: 8 hours continuous; Moonlight: 20 days continuous		
FL STANDARD	HIGH	LOW
	140 LUMENS	47 LUMENS
	4h	15h
	379m	219m
	36,000cd	12,000cd

Rechargeable Model	
	Class I, Div. 1, Groups C & D T4 Class I, Div. 2, Groups A, B, C, D T4 Class II, Div. 2, Groups F & G Class III T4
	Class I, Div. 1, Groups C & D T4 "Exia" Class I, Div. 2, Groups A, B, C, D, T4 Class II, Div. 2, Groups F & G Class III T4
NFPA	Rack meets requirements of 1901-14.1.1.1.2 (2003) mounted in any position
CE	Meets applicable European Community Directives

Alkaline Model	
	Class I, Div. 1, Groups C & D T4 Class I, Div. 2, Groups A, B, C, D, T4 Class II, Div. 2, Groups F & G Class III T4
	Class I, Div. 1, Groups C & D T4 "Exia" Class I, Div. 2, Groups A, B, C, D, T4 Class II, Div. 2, Groups F & G Class III T4
MSHA	Permissible Flashlight; (with alkaline batteries only). Approval No. 20-A100001-0 Tested for Intrinsic Safety in Methane-Air mixtures only.

Item	UPC	Part #
Steady Charge with AC/DC charger/holder		
Survivor LED 230V - Yellow	080926-90515-3	90515
Survivor LED 240V - Yellow	080926-90516-0	90516
Survivor LED 120V - Yellow	080926-90513-9	90513
Survivor LED 100 - Yellow	080926-90517-1	90517
Survivor LED 230V - Orange	080926-90505-4	90505
Survivor LED 230V - Orange (ATEX)	080926-90548-1	90548
Survivor LED 240V - Orange	080926-90506-1	90506
Survivor LED 240V - Orange (ATEX)	080926-90549-8	90549
Survivor LED 120V - Orange	080926-90503-0	90503
Survivor LED 100V - Orange	080926-90507-8	90507
Survivor LED 100V - Orange (ATEX)	080926-90550-4	90550
Survivor LED 230V - Black	080926-90525-2	90525
Survivor LED 240V - Black	080926-90526-9	90526
Survivor LED 120V - Black	080926-90523-8	90523
Survivor LED 100V - Black	080926-90527-6	90527

Assembled in USA

Item	UPC	Part #
Fast Charge with AC		
Survivor LED 230V - Yellow	080926-90514-6	90514
Survivor LED 120V - Yellow	080926-90512-2	90512
Survivor LED 230V - Orange	080926-90504-7	90504
Survivor LED 230V - Orange (ATEX)	080926-90551-1	90551
Survivor LED 120V - Orange	080926-90502-3	90502
Survivor LED 230V - Black	080926-90524-5	90524
Survivor LED 120V - Black	080926-90522-1	90522
Fast Charge with DC		
Survivor LED - Yellow	080926-90519-1	90519
Survivor LED - Orange (ATEX)	080926-90552-8	90552
Survivor LED - Black	080926-90528-3	90528
Survivor LED - Orange	080926-90509-2	90509
Without Charger		
Survivor LED - Yellow	080926-90510-8	90510
Survivor LED - Orange	080926-90500-7	90500
Survivor LED - Orange (ATEX)	080926-90553-5	90553
Survivor LED - Black	080926-90520-7	90520
Alkaline Model		
Survivor LED - Yellow	080926-90541-2	90541
Survivor LED - Orange	080926-90540-5	90540
Survivor LED - Orange (ATEX)	080926-90555-9	90555
Survivor LED - Black	080926-90545-0	90545

See reverse for additional part numbers





Item	UPC	Part #
DC2 direct wire charge cord (All Rechargeables)	080926-22050-8	22050
DC1 Charge Cord (All Rechargeables)	080926-22051-5	22051
120V AC charge cord	080926-22311-0	22311
240V AC charge cord	080926-22241-0	22241
230V AC charge cord	080926-22664-7	22664
100V AC charge cord	080926-22666-1	22666
Steady Charge (SC) Plug-In Charger Holder **Cords not included	080926-90010-3	90010
AC Fast Charger (Includes Holder)	080926-90011-0	90011
DC #1 Fast Charger (Includes Holder)	080926-90012-7	90012
DC #2 Fast Charger (Includes Holder)	080926-90013-4	90013
Steady Charge (SC) PiggyBack® Charger **Cords not included	080926-90110-0	90110
AC PiggyBack® Fast Charger	080926-90111-7	90111
DC #1 PiggyBack® Fast Charger	080926-90112-4	90112
DC #2 PiggyBack® Fast Charger	080926-90113-1	90113
Battery Pack Assembly (Blue Sleeve, NiCd Battery) Div 1	080926-90130-8	90130
Battery Pack Assembly (Black Sleeve, NiCd Battery) Div 2	080926-90338-8	90338
Bank Charger (SC) 120V AC	080926-90400-2	90400
Bank Charger (SC) 230V AC	080926-90600-6	90600
Bank Charger DC	080926-90401-9	90401
Survivor LED alkaline battery pack (Batteries not included)	080926-90542-9	90542



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
 www.streamlight.com ©Streamlight, Inc. Survivor LED 8/12