

15" Rack Mount

Color LCD Flat Panel with NTSC/PAL, S-Video

Display Performance



Dot pitch	0.297 mm
Display Colors (max)	16,700,000
Luminance	450 (cd/m2)
Contrast Ratio	300:1
Display Modes	640 x 350, 640 x 400, 640 x 480, 720 x 400, 800 x 600, 832 x 624, 1024 x 768
Active Display Area	(H) 304.1 mm x (V) 228.1 mm
Viewing Angle	140° Horizontal, 125° Vertical
On Screen Display	Power, Menu, Select/Up/Down/+/-/Source/IR
Video Input	Video - Analog RGB 0.7Vp-p/75 ohm, Sync-Separate, Positive or Negative TTL, Sync on Green
Scanning Frequency	(H) 15kHz-61kHz; (V) 50Hz (I) - 75Hz
Response Time	5 msec
Input Terminal	Mini D-Sub 15 pin, NTSC/PAL, S-Video
Power Source	88-260VAC auto sensing
Power Consumption	28 Watts, power saving mode - 5 Watts
Dimensions	12.25" high x 19" wide
Weight	10 lbs
Operating Environment	-0°C - 50°C 10 - 85% humidity w/o condensation
Storage Environment	-20°C - 60°C 10 - 95% humidity w/o condensation
Shock	100G half sine wave 2ms, one time each direction
Altitude	12,000 feet operating 40,000 feet storage

Product Information

Product	15" TFT Color LCD Flat Panel Display with NTSC/PAL, S-Video
Model Number	RP-15RM-SA

OPTIONS

- Touchscreen
- Protective glass
- Custom colors
- Private labeling, logos