

# 19" Rack Mount

Color LCD Flat Panel with NTSC, SVHS, S-Video, DVI

## Display Performance



Dot pitch	0.29 mm
Display Colors (max)	16,700,000
Luminance	250 (cd/m2)
Contrast Ratio	400:1
Display Modes	640 x 350, 640 x 400, 640 x 480, 720 x 400, 800 x 600, 832 x 624, 1024 x 768, 1152 x 900, 1280 x 1024 (1280 x 1024 recommended)
Viewing Angle	176° Horizontal, 176° Vertical
Pixel Arrangement	RGB vertical stripe
Video Input	Video - Analog RGB 0.7Vp-p, TTL Separate, Composite
Scanning Frequency	(H) 30kHz-92kHz; (V) 50Hz - 120Hz
Response Time	12 msec
Input Terminal	D-Sub, SVHS, S-Video, DVI, NTSC/PAL
Power Source	90-264V, 50/60Hz auto sensing
Power Consumption	22.76 Watts
Dimensions	15.75" high x 19" wide x: 3" deep
Weight	20 lbs
Operating Environment	0°C - 50°C 10% - 90% relative humidity (non-condensing)
Storage Environment	-20°C - 65°C 5% - 90% relative humidity (non-condensing)
Shock	50G half sine wave 2ms, one time each direction
Altitude	15,000 operating 30,000 storage

## Product Information

Product	19.1" a-Si Active Matrix TFT Color LCD Panel with NTSC/PAL S-Video, DVI, SVHS
Model Number	RP-19RM-LG

### OPTIONS

- Touchscreen
- Protective glass
- Custom colors
- Private labeling, logos
- -48V DC power