

# Water Heaters

## Wide Range of High Capacity Water Heaters

Water heaters designed for the marine environment in a range of capacities and material finishes

Available in The Americas only



**Robust**  
- Marine grade materials  
White epoxy coated, Stainless Steel  
or Marine Galvanised Steel

**Multiple Options**  
- Range of capacities and  
heat exchanger options

**Safety First**  
- Fixed temperature and  
pressure monitor for peace of mind

S300EW



White Epoxy Coated  
**Horizontal with Side Heat  
Exchanger Model**



White Epoxy Coated  
**Horizontal Electric  
Only Model**



Marine Galvanised Steel  
**Horizontal Rear Heat  
Exchanger Model**



Stainless Steel  
**Front Heat  
Exchanger Model**

### **i** Product Information

#### Model Specifications

Model		Capacity US Gals	Orientation	Heat Exchanger	PSI Rating	Overall Dimensions inches (W,D,H)	Exterior Material	Weights (lbs)
120 V	240 V							
S300W		11 lts (3 gal)	Horizontal	Side	100 psi	14.5" x 14" x 13"	White Epoxy	14
S300EW	S350EW	11 lts (3 gal)	Horizontal	Electric	100 psi	14.5" x 14" x 13"	White Epoxy	14
F600	F650	23 lts (6 gal)	Horizontal	Front	100 psi	13" x 19" x 13"	Marine Galvanized Steel	26
F600W	F650W	23 lts (6 gal)	Horizontal	Front	100 psi	13" x 19" x 13"	White Epoxy	26
	F650WSR	23 lts (6 gal)	Horizontal	Front	75 psi	13" x 19" x 13"	White Epoxy	26
F700	F750	23 lts (6 gal)	Horizontal	Front	100 psi	13" x 19" x 13"	Stainless Steel	24
S600	S650	23 lts (6 gal)	Horizontal	Rear	100 psi	13" x 19" x 13"	Marine Galvanized Steel	26
S600W	S650W	23 lts (6 gal)	Horizontal	Rear	100 psi	13" x 19" x 13"	White Epoxy	26
S600EW		23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	White Epoxy	26
	S650E	23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	Marine Galvanized Steel	26
	S650EW -3000	23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	White Epoxy	26
S700	S750	23 lts (6 gal)	Horizontal	Rear	100 psi	13" x 19" x 13"	Stainless Steel	24
S700E	S750E	23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	Stainless Steel	24

Note: All Whale Water Heaters must be installed and serviced by a qualified electrician in accordance with the Whale appliance installation and operating instructions and appropriate electrical regulations and certifications.

## Combination Electric/Heat Exchanger Or Electric Only Models

- Capacities available 3,6,11,20 and 28 US Gals
- Robust manufacturing
  - Hold down brackets welded to inner tank
- Double wall heat exchangers
  - Prevents accidental contamination of freshwater supply
- Safety controls
  - Integrated pressure relief valve and temperature monitor
- Sturdy, robust exteriors
  - Produced from marine grade stainless steel or epoxy coated
- Ignition protected
- Available in The Americas only

**2 Year Warranty**

### Model Specifications

Model		Orientation	Heat Exchanger	Capacity (US Gals)	PSI Rating	Overall Dimensions inches (W,D,H)	Exterior Material	Shipping Weight (lbs)
120 V	240 V							
F1100	F1150	Horizontal	Front	11	100 psi	16"x 22" x 16"	Marine Galvanized Steel	34
F1100W	F1150W	Horizontal	Front	11	100 psi	16"x 22" x 16"	White Epoxy	34
	F1150WSR	Horizontal	Front	11	75 psi	16"x 22" x 16"	White Epoxy	34
F1200	F1250	Horizontal	Front	11	100 psi	16"x 22" x 16"	Stainless Steel	32
S1100	S1150	Horizontal	Rear	11	100 psi	16"x 22" x 16"	Marine Galvanized Steel	34
S1200	S1250	Horizontal	Rear	11	100 psi	16"x 22" x 16"	Stainless Steel	32
	H2050	Horizontal	Rear	20	100 psi	16"x 32" x 16"	Marine Galvanized Steel	48
	H2050EW	Horizontal	Electric	20	100 psi	16"x 32" x 16"	White Epoxy	48
	H2050EW-3000	Horizontal	Electric	20	100 psi	16"x 32" x 16"	White Epoxy	48
	H2050EW-4500	Horizontal	Electric	20	100 psi	16"x 32" x 16"	White Epoxy	48
H2200		Horizontal	Rear	20	100 psi	16"x 32" x 16"	Stainless Steel	47
	H2250E	Horizontal	Electric	20	100 psi	16"x 32" x 16"	Stainless Steel	47
HF2000	HF2050	Horizontal	Front	20	100 psi	16"x 32" x 16"	Marine Galvanized Steel	48
HF2200	HF2250	Horizontal	Front	20	75 psi	16"x 32" x 16"	Stainless Steel	47
S1800	S1850	Vertical	Front	20	100 psi	20.25"x 20" x 27"	Marine Galvanized Steel	46
S1800W	S1850W	Vertical	Front	20	100 psi	20.25"x 20" x 27"	White Epoxy	46
	S1850EW	Vertical	Electric	20	100 psi	20.25"x 20" x 27"	White Epoxy	46
	S1850WSR	Vertical	Front	20	75 psi	20.25"x 20" x 27"	White Epoxy	46
S1900	S1950	Vertical	Front	20	100 psi	20.25"x 20" x 27"	Stainless Steel	45
S1900E		Vertical	Electric	20	100 psi	20.25"x 20" x 27"	Stainless Steel	45
	H2850ES-3000	Horizontal	Electric	28	100 psi	16"x 40" x 16"	Stainless Steel	59
	H2850ES-4500	Horizontal	Electric	28	100 psi	16"x 40" x 16"	Stainless Steel	59
	H2850EW-3000	Horizontal	Electric	28	100 psi	16"x 40" x 16"	White Epoxy	59
	H2850EW-4500	Horizontal	Electric	28	100 psi	16"x 40" x 16"	White Epoxy	59

NOTE: All models in available in The Americas only.

S300W - 1250W element and requires a 15A Circuit Breaker

3000 and 4500 models have a 3000W and 4000W element respectively and requires a 15A Dual Breaker (3000) or 20A Dual Breaker (4500)

All other models have a 1500W element and require a 15A Circuit Breaker (120V) or 10A Dual Breaker (240V)

Note: All Whale Water Heaters must be installed and serviced by a qualified electrician in accordance with the Whale appliance installation and operating instructions and appropriate electrical regulations and certifications.