



Model Number: 986DIP
Dimensions: 11-5/8" H x 9-3/8" W x 6-1/4" D
Enclosure: Yellow, NEMA 4 Fiberglass, Surface Mount



Model Number: 986DIPP
Dimensions: 11-5/8" H x 9-3/8" W x 6-1/4" D
Enclosure: Yellow, NEMA 4 Fiberglass, Surface Mount



Model Number: 984RIP
Dimensions: 9-7/8" H x 6-5/8" W x 3-1/4" D
Enclosure: Red, NEMA 4 Fiberglass, Surface Mount



Model Number: 984RIPP
Dimensions: 9-7/8" H x 6-5/8" W x 3-1/4" D
Enclosure: Red, NEMA 4 Fiberglass, Surface Mount



Model Number: 976GIP
Dimensions: 11-7/16" H x 13-9/16" W x 5-1/4" D
Enclosure: Gray, NEMA 4 Fiberglass, Surface Mount



Model Number: 976GIPP
Dimensions: 11-7/16" H x 13-9/16" W x 5-1/4" D
Enclosure: Gray, NEMA 4 Fiberglass, Surface Mount

Phone Specifications

- Includes 10/100 PoE 802.3af Ethernet Connection
- Designed to be powered from PoE
- Programmable to call Base Station
- On-site programming, web based programming requires laptop computer
- Temperature range -40° F to 150° F
- Automatic dialer
- Fully automated operation
- Automatic answer feature
- Audible and visual indication
- Braille label

Camera Specifications

- Mounted by RATH® on the flush plate
- Continuous stream or upon phone activation
- 180° viewing angle is field adjustable
- High resolution at 600 TVL
- Excellent video in low light conditions (.0001 Lux/F2.0)
- Ethernet connection
- Powered by PoE