



Yellow Call Box 2100-986 Series

Product Specifications

1.0 General Description

- 1.1 The Yellow Call Box shall be square in appearance and made of a vandal resistant and NEMA 4 rated fiberglass enclosure. The Call Box uses a push button for activation and a red LED for an indication of activation. The word 'EMERGENCY' down the left and 'TELEPHONE' down the right shall be vertically mounted in industrial strength decals.
- 1.2 The emergency communication component shall comply with the American with Disabilities Act (ADA). The phone shall have the ability to be programmed with up to 5 emergency phone numbers. Upon activation of the emergency push button, a call will be automatically placed; two-way communication shall then open up after a location message is played. The call can only be disconnected by the called party.

2.0 Construction

- 2.1 The Yellow Call Box shall be constructed of a vandal resistant and NEMA 4 outdoor rated housing.
- 2.2 The Yellow Call Box measures 11 5/8" high, 9 3/8" wide and 6 1/4" deep.
- 2.3 The Yellow Call Box contains a speaker phone button which shall be located no more than 48" above the ground to ensure conformance with ADA requirements.
- 2.4 The Yellow Call Box must have a Braille faceplate stating 'EMERGENCY PHONE' 'PUSH FOR HELP' to ensure conformance with ADA requirements.
- 2.5 The Yellow Call Box shall support optional use of a remote mounted strobe that will flash when the call box is activated.

3.0 Mounting

- 3.1 The Yellow Call Box shall be wall or pole mountable with a custom made, aluminum, Pole Mount Bracket (7005A).



Yellow Call Box 2100-986 Series

Product Specifications

4.0 Electrical

- 4.1 The Yellow Call Box shall be powered by 120vac or 12vdc.
- 4.2 The strobe (optional accessory) shall be powered off 12vdc using Yellow Call Box phone relay (optional accessory). (P#2100-986DAI includes 12v relay)

5.0 Lights

- 5.1 The 12v strobe light (optional accessory P#7008B-12v) shall be remote mountable on a wall or pole using a custom STROBE MOUNTING KIT. The strobe shall be activated upon pushing of the emergency phone button.
- 5.2 The strobe shall have an LED cluster and flash at a rate of a minimum of 60 flashes per minute.
- 5.3 A dual element Beacon/Strobe light shall be offered as an option (P#7010B-12v). The dual element will have a constant-on LED for allowing continuous, steady illumination. The strobe element will activate upon the pushing of the emergency phone button.

6.0 Communications

- 6.1 The unit shall have an ADA compliant and vandal resistant speaker phone.
- 6.2 The phone shall be a push once to talk phone. Once the button has been pushed, the phone will call a programmed phone emergency number. The phone must be capable of being programmed with up to 5 emergency numbers, dialing them in sequence until one is answered.
- 6.3 The phone shall have Location Message capability. Phone must have a minimum 18 second recordable message capability programmable to play once, twice, or continuously until * is pressed by the called party. Phone shall notify called party of the location of the Yellow Call Box, upon it being received at the emergency dispatch center.



Yellow Call Box 2100-986 Series

Product Specifications

- 6.4 Phone shall be capable of allowing the called party to replay the phone location message if necessary to ensure an understanding of the location of the Call Box.
- 6.5 Once call has been made (button pushed), the call can only be terminated by the called party.
- 6.6 The Yellow Call Box must have a red LED that will light up upon push of the button. The light shall be a solid color when the phone is activated, and will flash when call has been answered.
- 6.7 The speakerphone must be capable of being programmed and reprogrammed on site and remotely.
- 6.8 Line powered phones and Dip Switch programming are not acceptable.
- 6.9 The phone must have a built in phone line consolidator feature. Phones must be capable of sharing phone lines with up to 10 Rath Security SmartPhones if required by end user to reduce operational cost.
- 6.10 Standard Phone features:
- Programmable with up to 5 emergency phone numbers
 - Weatherproof speaker
 - Weatherproof microphone
 - Operating temperature of between -40°F to +150°F (-40° to + 65°C)
 - Programmable passwords
 - On-site or remote programmable
 - EEPROM memory to protect programming
 - Adjustable speaker and microphones levels
 - Programmable location message with human voice recognition
 - Programmable conversation time
 - 2 button – 2 number capability
 - Remote and on-site diagnostic testing
 - Ability to control additional accessories (cameras, speakers)



Yellow Call Box 2100-986 Series

Product Specifications

7.0 Finish

- 7.1 Unit shall be of a Safety Yellow dyed fiberglass finish.
- 7.2 Unit must be UV resistant.

8.0 Graphics

- 8.1 All wording shall distinctly identify the Yellow Call Box as an 'EMERGENCY TELEPHONE'.
- 8.2 Yellow Call Box finish shall be UV protected.

9.0 Options

- 9.1 System must allow for custom lettering in place of "EMERGENCY TELEPHONE" if requested.
- 9.2 Both remote dome cameras and 'pinhole' camera options must be available from manufacturer.
- 9.3 Strobes must be available in custom colors.
- 9.4 Communication options shall include Analog, Cellular, VoIP, WIFI VoIP, and 900 MHz.

10.0 Warranty

- 10.1 The unit shall be warranted from all factory defects for a period of two years.

11.0 Manufacturer

The manufacturer shall be:
RATH® Security
N56 W24720 North Corporate Circle
Sussex, WI 53089
800-451-1460
Website: www.rathsecurity.com