



## Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

### Grades BQ / BX

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
<b>BQ Grade 99.99% Efficiency at 0.3 microns</b>				
050-05-BQ	12-32-50K	6G04-013X10	0.50	1.25
050-11-BQ	12-57-50K	6G04-023X10	0.50	2.25
100-09-BQ	25-51-50K		1.00	2.00
100-12-BQ	25-64-50K	6G04-025X10	1.00	2.50
100-18-BQ	25-127-50K		1.00	5.00
100-25-BQ	25-178-50K	6T10-070X10	1.00	7.00
150-19-BQ	38-152-50K	6T15-060X10	1.50	6.00
200-16-BQ	51-89-50K		2.00	3.50
200-30-BQ	51-213-50K		2.00	8.40
200-35-BQ	51-230-50K	6T20-090X10	2.00	9.00
200-80-BQ	51-476-50K	6T20-187X10	2.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
<b>BX Grade 99.99% Efficiency at 0.3 microns</b>				
050-05-BX	12-32-50C	6H04-013X10	0.50	1.25
050-11-BX	12-57-50C	6H04-023X10	0.50	2.25
100-09-BX	25-51-50C	6H10-020X8	1.00	2.00
100-12-BX	25-64-50C	6H10-025X8	1.00	2.50
100-18-BX	25-127-50C	6H10-050X4	1.00	5.00
100-25-BX	25-178-50C	6H10-070X4	1.00	7.00
150-19-BX	38-152-50C	6H15-060X4	1.50	6.00
200-16-BX	51-89-50C	6H20-035X4	2.00	3.50
200-30-BX	51-213-50C		2.00	8.40
200-35-BX	51-230-50C	6H20-090X2	2.00	9.00
200-75-BX	51-460-50C		2.00	18.00
200-80-BX	51-476-50C	6H20-187X1	2.00	18.75

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



## Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

### Grades BQ / BX

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
BQ Grade 99.99% Efficiency at 0.3 microns				
050-05-BQ	12-32-50K	6G04-013X10	0.50	1.25
050-11-BQ	12-57-50K	6G04-023X10	0.50	2.25
100-09-BQ	25-51-50K		1.00	2.00
100-12-BQ	25-64-50K	6G04-025X10	1.00	2.50
100-18-BQ	25-127-50K		1.00	5.00
100-25-BQ	25-178-50K	6T10-070X10	1.00	7.00
150-19-BQ	38-152-50K	6T15-060X10	1.50	6.00
200-16-BQ	51-89-50K		2.00	3.50
200-30-BQ	51-213-50K		2.00	8.40
200-35-BQ	51-230-50K	6T20-090X10	2.00	9.00
200-80-BQ	51-476-50K	6T20-187X10	2.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
BX Grade 99.99% Efficiency at 0.3 microns				
050-05-BX	12-32-50C	6H04-013X10	0.50	1.25
050-11-BX	12-57-50C	6H04-023X10	0.50	2.25
100-09-BX	25-51-50C	6H10-020X8	1.00	2.00
100-12-BX	25-64-50C	6H10-025X8	1.00	2.50
100-18-BX	25-127-50C	6H10-050X4	1.00	5.00
100-25-BX	25-178-50C	6H10-070X4	1.00	7.00
150-19-BX	38-152-50C	6H15-060X4	1.50	6.00
200-16-BX	51-89-50C	6H20-035X4	2.00	3.50
200-30-BX	51-213-50C		2.00	8.40
200-35-BX	51-230-50C	6H20-090X2	2.00	9.00
200-75-BX	51-460-50C		2.00	18.00
200-80-BX	51-476-50C	6H20-187X1	2.00	18.75

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.