



Balston – Headline Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades AAQ / AQ

BALSTON	HEADLINE	Inside Diameter	Overall Length
AAQ Grade 99.998% Efficiency at 0.3 microns			
050-05-AAQ	12-32-30K	0.50	1.25
050-11-AAQ	12-57-30K	0.50	2.25
100-09-AAQ	25-51-30K	1.00	2.00
100-12-AAQ	25-64-30K	1.00	2.50
100-18-AAQ	25-127-30K	1.00	5.00
100-25-AAQ	25-178-30K	1.00	7.00
150-19-AAQ	38-152-30K	1.50	6.00
200-16-AAQ	51-89-30K	2.00	3.50
200-30-AAQ	51-213-30K	2.00	8.40
200-35-AAQ	51-230-30K	2.00	9.00
200-80-AAQ	51-476-30K	2.00	18.00
BALSTON	HEADLINE	Inside Diameter	Overall Length
AQ Grade 99.998% Efficiency at 0.3 microns			
050-05-AQ	12-32-40K	0.50	1.25
050-11-AQ	12-57-40K	0.50	2.25
100-09-AQ	25-51-40K	1.00	2.00
100-12-AQ	25-64-40K	1.00	2.50
100-18-AQ	25-127-40K	1.00	5.00
100-25-AQ	25-178-40K	1.00	7.00
150-19-AQ	38-152-40K	1.50	6.00
200-16-AQ	51-89-40K	2.00	3.50
200-30-AQ	51-213-40K	2.00	8.40
200-35-AQ	51-230-40K	2.00	9.00
200-80-AQ	51-476-40K	2.00	18.00

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



Balston – Headline Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades AAQ / AQ

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
AAQ Grade 99.998% Efficiency at 0.3 microns				
050-05-AAQ	12-32-30K		0.50	1.25
050-11-AAQ	12-57-30K		0.50	2.25
100-09-AAQ	25-51-30K		1.00	2.00
100-12-AAQ	25-64-30K		1.00	2.50
100-18-AAQ	25-127-30K		1.00	5.00
100-25-AAQ	25-178-30K		1.00	7.00
150-19-AAQ	38-152-30K		1.50	6.00
200-16-AAQ	51-89-30K		2.00	3.50
200-30-AAQ	51-213-30K		2.00	8.40
200-35-AAQ	51-230-30K		2.00	9.00
200-80-AAQ	51-476-30K		2.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
AQ Grade 99.998% Efficiency at 0.3 microns				
050-05-AQ	12-32-40K		0.50	1.25
050-11-AQ	12-57-40K		0.50	2.25
100-09-AQ	25-51-40K		1.00	2.00
100-12-AQ	25-64-40K		1.00	2.50
100-18-AQ	25-127-40K		1.00	5.00
100-25-AQ	25-178-40K		1.00	7.00
150-19-AQ	38-152-40K		1.50	6.00
200-16-AQ	51-89-40K		2.00	3.50
200-30-AQ	51-213-40K		2.00	8.40
200-35-AQ	51-230-40K		2.00	9.00
200-80-AQ	51-476-40K		2.00	18.00

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.