



## Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

### Grades DQ / DX

| BALSTON                                       | HEADLINE   | FINITE       | Inside Diameter | Overall Length |
|---|------------|--------------|-----------------|----------------|
| <b>DQ Grade 95% Efficiency at 0.3 microns</b> |            |              |                 |                |
| 050-05-DQ                                     | 12-32-70K  |              | 0.50            | 1.25           |
| 050-11-DQ                                     | 12-57-70K  |              | 0.50            | 2.25           |
| 100-09-DQ                                     | 25-51-70K  |              | 1.00            | 2.00           |
| 100-12-DQ                                     | 25-64-70K  |              | 1.00            | 2.50           |
| 100-18-DQ                                     | 25-127-70K |              | 1.00            | 5.00           |
| 100-25-DQ                                     | 25-178-70K |              | 1.00            | 7.00           |
| 150-19-DQ                                     | 38-152-70K |              | 1.50            | 6.00           |
| 200-16-DQ                                     | 51-89-70K  |              | 2.00            | 3.50           |
| 200-30-DQ                                     | 51-213-70K |              | 2.00            | 8.40           |
| 200-35-DQ                                     | 51-230-70K |              | 2.00            | 9.00           |
| 200-80-DQ                                     | 51-476-70K |              | 2.00            | 18.00          |
|   |            |              |                 |                |
| BALSTON                                       | HEADLINE   | FINITE       | Inside Diameter | Overall Length |
| <b>DX Grade 95% Efficiency at 0.3 microns</b> |            |              |                 |                |
| 050-05-DX                                     | 12-32-70C  |              | 0.50            | 1.25           |
| 050-11-DX                                     | 12-57-70C  | 10H04-013X10 | 0.50            | 2.25           |
| 100-09-DX                                     | 25-51-70C  | 10H04-023X10 | 1.00            | 2.00           |
| 100-12-DX                                     | 25-64-70C  | 10H10-020X8  | 1.00            | 2.50           |
| 100-18-DX                                     | 25-127-70C | 10H10-025X8  | 1.00            | 5.00           |
| 100-25-DX                                     | 25-178-70C | 10H10-050X4  | 1.00            | 7.00           |
| 150-19-DX                                     | 38-152-70C | 10H10-070X4  | 1.50            | 6.00           |
| 200-16-DX                                     | 51-89-70C  | 10H15-060X4  | 2.00            | 3.50           |
| 200-30-DX                                     | 51-213-70C | 10H20-035X4  | 2.00            | 8.40           |
| 200-35-DX                                     | 51-230-70C | 10H20-090X2  | 2.00            | 9.00           |
| 200-75-DX                                     | 51-460-70C |              | 2.00            | 18.00          |
| 200-80-DX                                     | 51-476-70C | 10H20-187X1  | 2.00            | 18.75          |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



## Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

### Grades DQ / DX

| BALSTON                                | HEADLINE   | FINITE       | Inside Diameter | Overall Length |
|--|------------|--------------|-----------------|----------------|
| DQ Grade 95% Efficiency at 0.3 microns |            |              |                 |                |
| 050-05-DQ                              | 12-32-70K  |              | 0.50            | 1.25           |
| 050-11-DQ                              | 12-57-70K  |              | 0.50            | 2.25           |
| 100-09-DQ                              | 25-51-70K  |              | 1.00            | 2.00           |
| 100-12-DQ                              | 25-64-70K  |              | 1.00            | 2.50           |
| 100-18-DQ                              | 25-127-70K |              | 1.00            | 5.00           |
| 100-25-DQ                              | 25-178-70K |              | 1.00            | 7.00           |
| 150-19-DQ                              | 38-152-70K |              | 1.50            | 6.00           |
| 200-16-DQ                              | 51-89-70K  |              | 2.00            | 3.50           |
| 200-30-DQ                              | 51-213-70K |              | 2.00            | 8.40           |
| 200-35-DQ                              | 51-230-70K |              | 2.00            | 9.00           |
| 200-80-DQ                              | 51-476-70K |              | 2.00            | 18.00          |
|  |            |              |                 |                |
| BALSTON                                | HEADLINE   | FINITE       | Inside Diameter | Overall Length |
| DX Grade 95% Efficiency at 0.3 microns |            |              |                 |                |
| 050-05-DX                              | 12-32-70C  |              | 0.50            | 1.25           |
| 050-11-DX                              | 12-57-70C  | 10H04-013X10 | 0.50            | 2.25           |
| 100-09-DX                              | 25-51-70C  | 10H04-023X10 | 1.00            | 2.00           |
| 100-12-DX                              | 25-64-70C  | 10H10-020X8  | 1.00            | 2.50           |
| 100-18-DX                              | 25-127-70C | 10H10-025X8  | 1.00            | 5.00           |
| 100-25-DX                              | 25-178-70C | 10H10-050X4  | 1.00            | 7.00           |
| 150-19-DX                              | 38-152-70C | 10H10-070X4  | 1.50            | 6.00           |
| 200-16-DX                              | 51-89-70C  | 10H15-060X4  | 2.00            | 3.50           |
| 200-30-DX                              | 51-213-70C | 10H20-035X4  | 2.00            | 8.40           |
| 200-35-DX                              | 51-230-70C | 10H20-090X2  | 2.00            | 9.00           |
| 200-75-DX                              | 51-460-70C |              | 2.00            | 18.00          |
| 200-80-DX                              | 51-476-70C | 10H20-187X1  | 2.00            | 18.75          |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.