



Balston – Headline Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades AAQ / AQ

| BALSTON | HEADLINE | Inside Diameter | Overall Length |
|--|------------|-----------------|----------------|
| AAQ Grade 99.998% Efficiency at 0.3 microns | | | |
| 050-05-AAQ | 12-32-30K | 0.50 | 1.25 |
| 050-11-AAQ | 12-57-30K | 0.50 | 2.25 |
| 100-09-AAQ | 25-51-30K | 1.00 | 2.00 |
| 100-12-AAQ | 25-64-30K | 1.00 | 2.50 |
| 100-18-AAQ | 25-127-30K | 1.00 | 5.00 |
| 100-25-AAQ | 25-178-30K | 1.00 | 7.00 |
| 150-19-AAQ | 38-152-30K | 1.50 | 6.00 |
| 200-16-AAQ | 51-89-30K | 2.00 | 3.50 |
| 200-30-AAQ | 51-213-30K | 2.00 | 8.40 |
| 200-35-AAQ | 51-230-30K | 2.00 | 9.00 |
| 200-80-AAQ | 51-476-30K | 2.00 | 18.00 |
| | | | |
| BALSTON | HEADLINE | Inside Diameter | Overall Length |
| AQ Grade 99.998% Efficiency at 0.3 microns | | | |
| 050-05-AQ | 12-32-40K | 0.50 | 1.25 |
| 050-11-AQ | 12-57-40K | 0.50 | 2.25 |
| 100-09-AQ | 25-51-40K | 1.00 | 2.00 |
| 100-12-AQ | 25-64-40K | 1.00 | 2.50 |
| 100-18-AQ | 25-127-40K | 1.00 | 5.00 |
| 100-25-AQ | 25-178-40K | 1.00 | 7.00 |
| 150-19-AQ | 38-152-40K | 1.50 | 6.00 |
| 200-16-AQ | 51-89-40K | 2.00 | 3.50 |
| 200-30-AQ | 51-213-40K | 2.00 | 8.40 |
| 200-35-AQ | 51-230-40K | 2.00 | 9.00 |
| 200-80-AQ | 51-476-40K | 2.00 | 18.00 |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



Balston – Headline Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades AAQ / AQ

| BALSTON | HEADLINE | FINITE | Inside Diameter | Overall Length |
|---|------------|--------|-----------------|----------------|
| AAQ Grade 99.998% Efficiency at 0.3 microns | | | | |
| 050-05-AAQ | 12-32-30K | | 0.50 | 1.25 |
| 050-11-AAQ | 12-57-30K | | 0.50 | 2.25 |
| 100-09-AAQ | 25-51-30K | | 1.00 | 2.00 |
| 100-12-AAQ | 25-64-30K | | 1.00 | 2.50 |
| 100-18-AAQ | 25-127-30K | | 1.00 | 5.00 |
| 100-25-AAQ | 25-178-30K | | 1.00 | 7.00 |
| 150-19-AAQ | 38-152-30K | | 1.50 | 6.00 |
| 200-16-AAQ | 51-89-30K | | 2.00 | 3.50 |
| 200-30-AAQ | 51-213-30K | | 2.00 | 8.40 |
| 200-35-AAQ | 51-230-30K | | 2.00 | 9.00 |
| 200-80-AAQ | 51-476-30K | | 2.00 | 18.00 |
| | | | | |
| BALSTON | HEADLINE | FINITE | Inside Diameter | Overall Length |
| AQ Grade 99.998% Efficiency at 0.3 microns | | | | |
| 050-05-AQ | 12-32-40K | | 0.50 | 1.25 |
| 050-11-AQ | 12-57-40K | | 0.50 | 2.25 |
| 100-09-AQ | 25-51-40K | | 1.00 | 2.00 |
| 100-12-AQ | 25-64-40K | | 1.00 | 2.50 |
| 100-18-AQ | 25-127-40K | | 1.00 | 5.00 |
| 100-25-AQ | 25-178-40K | | 1.00 | 7.00 |
| 150-19-AQ | 38-152-40K | | 1.50 | 6.00 |
| 200-16-AQ | 51-89-40K | | 2.00 | 3.50 |
| 200-30-AQ | 51-213-40K | | 2.00 | 8.40 |
| 200-35-AQ | 51-230-40K | | 2.00 | 9.00 |
| 200-80-AQ | 51-476-40K | | 2.00 | 18.00 |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.