



Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades DQ / DX

| BALSTON | HEADLINE | FINITE | Inside Diameter | Overall Length |
|---|------------|--------------|-----------------|----------------|
| DQ Grade 95% Efficiency at 0.3 microns | | | | |
| 050-05-DQ | 12-32-70K | | 0.50 | 1.25 |
| 050-11-DQ | 12-57-70K | | 0.50 | 2.25 |
| 100-09-DQ | 25-51-70K | | 1.00 | 2.00 |
| 100-12-DQ | 25-64-70K | | 1.00 | 2.50 |
| 100-18-DQ | 25-127-70K | | 1.00 | 5.00 |
| 100-25-DQ | 25-178-70K | | 1.00 | 7.00 |
| 150-19-DQ | 38-152-70K | | 1.50 | 6.00 |
| 200-16-DQ | 51-89-70K | | 2.00 | 3.50 |
| 200-30-DQ | 51-213-70K | | 2.00 | 8.40 |
| 200-35-DQ | 51-230-70K | | 2.00 | 9.00 |
| 200-80-DQ | 51-476-70K | | 2.00 | 18.00 |
| | | | | |
| BALSTON | HEADLINE | FINITE | Inside Diameter | Overall Length |
| DX Grade 95% Efficiency at 0.3 microns | | | | |
| 050-05-DX | 12-32-70C | | 0.50 | 1.25 |
| 050-11-DX | 12-57-70C | 10H04-013X10 | 0.50 | 2.25 |
| 100-09-DX | 25-51-70C | 10H04-023X10 | 1.00 | 2.00 |
| 100-12-DX | 25-64-70C | 10H10-020X8 | 1.00 | 2.50 |
| 100-18-DX | 25-127-70C | 10H10-025X8 | 1.00 | 5.00 |
| 100-25-DX | 25-178-70C | 10H10-050X4 | 1.00 | 7.00 |
| 150-19-DX | 38-152-70C | 10H10-070X4 | 1.50 | 6.00 |
| 200-16-DX | 51-89-70C | 10H15-060X4 | 2.00 | 3.50 |
| 200-30-DX | 51-213-70C | 10H20-035X4 | 2.00 | 8.40 |
| 200-35-DX | 51-230-70C | 10H20-090X2 | 2.00 | 9.00 |
| 200-75-DX | 51-460-70C | | 2.00 | 18.00 |
| 200-80-DX | 51-476-70C | 10H20-187X1 | 2.00 | 18.75 |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades DQ / DX

| BALSTON | HEADLINE | FINITE | Inside Diameter | Overall Length |
|--|------------|--------------|-----------------|----------------|
| DQ Grade 95% Efficiency at 0.3 microns | | | | |
| 050-05-DQ | 12-32-70K | | 0.50 | 1.25 |
| 050-11-DQ | 12-57-70K | | 0.50 | 2.25 |
| 100-09-DQ | 25-51-70K | | 1.00 | 2.00 |
| 100-12-DQ | 25-64-70K | | 1.00 | 2.50 |
| 100-18-DQ | 25-127-70K | | 1.00 | 5.00 |
| 100-25-DQ | 25-178-70K | | 1.00 | 7.00 |
| 150-19-DQ | 38-152-70K | | 1.50 | 6.00 |
| 200-16-DQ | 51-89-70K | | 2.00 | 3.50 |
| 200-30-DQ | 51-213-70K | | 2.00 | 8.40 |
| 200-35-DQ | 51-230-70K | | 2.00 | 9.00 |
| 200-80-DQ | 51-476-70K | | 2.00 | 18.00 |
| | | | | |
| BALSTON | HEADLINE | FINITE | Inside Diameter | Overall Length |
| DX Grade 95% Efficiency at 0.3 microns | | | | |
| 050-05-DX | 12-32-70C | | 0.50 | 1.25 |
| 050-11-DX | 12-57-70C | 10H04-013X10 | 0.50 | 2.25 |
| 100-09-DX | 25-51-70C | 10H04-023X10 | 1.00 | 2.00 |
| 100-12-DX | 25-64-70C | 10H10-020X8 | 1.00 | 2.50 |
| 100-18-DX | 25-127-70C | 10H10-025X8 | 1.00 | 5.00 |
| 100-25-DX | 25-178-70C | 10H10-050X4 | 1.00 | 7.00 |
| 150-19-DX | 38-152-70C | 10H10-070X4 | 1.50 | 6.00 |
| 200-16-DX | 51-89-70C | 10H15-060X4 | 2.00 | 3.50 |
| 200-30-DX | 51-213-70C | 10H20-035X4 | 2.00 | 8.40 |
| 200-35-DX | 51-230-70C | 10H20-090X2 | 2.00 | 9.00 |
| 200-75-DX | 51-460-70C | | 2.00 | 18.00 |
| 200-80-DX | 51-476-70C | 10H20-187X1 | 2.00 | 18.75 |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.