



Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades CQ / CX

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
CQ Grade 99.5% Efficiency at 0.3 microns				
050-05-CQ	12-32-60K	8G04-013X10	0.50	1.25
050-11-CQ	12-57-60K	8G04-023X10	0.50	2.25
100-09-CQ	25-51-60K		1.00	2.00
100-12-CQ	25-64-60K	8G04-025X10	1.00	2.50
100-18-CQ	25-127-60K		1.00	5.00
100-25-CQ	25-178-60K	8T10-070X10	1.00	7.00
150-19-CQ	38-152-60K	8T15-060X10	1.50	6.00
200-16-CQ	51-89-60K		1.00	3.50
200-30-CQ	51-213-60K		1.00	8.40
200-35-CQ	51-230-60K	8T20-090X10	1.00	9.00
200-80-CQ	51-476-60K	8T20-187X10	1.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
CX Grade 99.5% Efficiency at 0.3 microns				
050-05-CX	12-32-60C	8H04-013X10	0.50	1.25
050-11-CX	12-57-60C	8H04-023X10	0.50	2.25
100-09-CX	25-51-60C	8H10-020X8	1.00	2.00
100-12-CX	25-64-60C	8H10-025X8	1.00	2.50
100-18-CX	25-127-60C	8H10-050X4	1.00	5.00
100-25-CX	25-178-60C	8H10-070X4	1.00	7.00
150-19-CX	38-152-60C	8H15-060X4	1.50	6.00
200-16-CX	51-89-60C	8H20-035X4	2.00	3.50
200-30-CX	51-213-60C		2.00	8.40
200-35-CX	51-230-60C	8H20-090X2	2.00	9.00
200-75-CX	51-460-60C		2.00	18.00
200-80-CX	51-476-60C	8H20-187X1	2.00	18.75

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades CQ / CX

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
CQ Grade 99.5% Efficiency at 0.3 microns				
050-05-CQ	12-32-60K	8G04-013X10	0.50	1.25
050-11-CQ	12-57-60K	8G04-023X10	0.50	2.25
100-09-CQ	25-51-60K		1.00	2.00
100-12-CQ	25-64-60K	8G04-025X10	1.00	2.50
100-18-CQ	25-127-60K		1.00	5.00
100-25-CQ	25-178-60K	8T10-070X10	1.00	7.00
150-19-CQ	38-152-60K	8T15-060X10	1.50	6.00
200-16-CQ	51-89-60K		1.00	3.50
200-30-CQ	51-213-60K		1.00	8.40
200-35-CQ	51-230-60K	8T20-090X10	1.00	9.00
200-80-CQ	51-476-60K	8T20-187X10	1.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
CX Grade 99.5% Efficiency at 0.3 microns				
050-05-CX	12-32-60C	8H04-013X10	0.50	1.25
050-11-CX	12-57-60C	8H04-023X10	0.50	2.25
100-09-CX	25-51-60C	8H10-020X8	1.00	2.00
100-12-CX	25-64-60C	8H10-025X8	1.00	2.50
100-18-CX	25-127-60C	8H10-050X4	1.00	5.00
100-25-CX	25-178-60C	8H10-070X4	1.00	7.00
150-19-CX	38-152-60C	8H15-060X4	1.50	6.00
200-16-CX	51-89-60C	8H20-035X4	2.00	3.50
200-30-CX	51-213-60C		2.00	8.40
200-35-CX	51-230-60C	8H20-090X2	2.00	9.00
200-75-CX	51-460-60C		2.00	18.00
200-80-CX	51-476-60C	8H20-187X1	2.00	18.75

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.