



Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades BQ / BX

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
BQ Grade 99.99% Efficiency at 0.3 microns				
050-05-BQ	12-32-50K	6G04-013X10	0.50	1.25
050-11-BQ	12-57-50K	6G04-023X10	0.50	2.25
100-09-BQ	25-51-50K		1.00	2.00
100-12-BQ	25-64-50K	6G04-025X10	1.00	2.50
100-18-BQ	25-127-50K		1.00	5.00
100-25-BQ	25-178-50K	6T10-070X10	1.00	7.00
150-19-BQ	38-152-50K	6T15-060X10	1.50	6.00
200-16-BQ	51-89-50K		2.00	3.50
200-30-BQ	51-213-50K		2.00	8.40
200-35-BQ	51-230-50K	6T20-090X10	2.00	9.00
200-80-BQ	51-476-50K	6T20-187X10	2.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
BX Grade 99.99% Efficiency at 0.3 microns				
050-05-BX	12-32-50C	6H04-013X10	0.50	1.25
050-11-BX	12-57-50C	6H04-023X10	0.50	2.25
100-09-BX	25-51-50C	6H10-020X8	1.00	2.00
100-12-BX	25-64-50C	6H10-025X8	1.00	2.50
100-18-BX	25-127-50C	6H10-050X4	1.00	5.00
100-25-BX	25-178-50C	6H10-070X4	1.00	7.00
150-19-BX	38-152-50C	6H15-060X4	1.50	6.00
200-16-BX	51-89-50C	6H20-035X4	2.00	3.50
200-30-BX	51-213-50C		2.00	8.40
200-35-BX	51-230-50C	6H20-090X2	2.00	9.00
200-75-BX	51-460-50C		2.00	18.00
200-80-BX	51-476-50C	6H20-187X1	2.00	18.75

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades CQ / CX

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
CQ Grade 99.5% Efficiency at 0.3 microns				
050-05-CQ	12-32-60K	8G04-013X10	0.50	1.25
050-11-CQ	12-57-60K	8G04-023X10	0.50	2.25
100-09-CQ	25-51-60K		1.00	2.00
100-12-CQ	25-64-60K	8G04-025X10	1.00	2.50
100-18-CQ	25-127-60K		1.00	5.00
100-25-CQ	25-178-60K	8T10-070X10	1.00	7.00
150-19-CQ	38-152-60K	8T15-060X10	1.50	6.00
200-16-CQ	51-89-60K		1.00	3.50
200-30-CQ	51-213-60K		1.00	8.40
200-35-CQ	51-230-60K	8T20-090X10	1.00	9.00
200-80-CQ	51-476-60K	8T20-187X10	1.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
CX Grade 99.5% Efficiency at 0.3 microns				
050-05-CX	12-32-60C	8H04-013X10	0.50	1.25
050-11-CX	12-57-60C	8H04-023X10	0.50	2.25
100-09-CX	25-51-60C	8H10-020X8	1.00	2.00
100-12-CX	25-64-60C	8H10-025X8	1.00	2.50
100-18-CX	25-127-60C	8H10-050X4	1.00	5.00
100-25-CX	25-178-60C	8H10-070X4	1.00	7.00
150-19-CX	38-152-60C	8H15-060X4	1.50	6.00
200-16-CX	51-89-60C	8H20-035X4	2.00	3.50
200-30-CX	51-213-60C		2.00	8.40
200-35-CX	51-230-60C	8H20-090X2	2.00	9.00
200-75-CX	51-460-60C		2.00	18.00
200-80-CX	51-476-60C	8H20-187X1	2.00	18.75

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



Balston – Headline – Parker-Finite Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades DQ / DX

BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
DQ Grade 95% Efficiency at 0.3 microns				
050-05-DQ	12-32-70K		0.50	1.25
050-11-DQ	12-57-70K		0.50	2.25
100-09-DQ	25-51-70K		1.00	2.00
100-12-DQ	25-64-70K		1.00	2.50
100-18-DQ	25-127-70K		1.00	5.00
100-25-DQ	25-178-70K		1.00	7.00
150-19-DQ	38-152-70K		1.50	6.00
200-16-DQ	51-89-70K		2.00	3.50
200-30-DQ	51-213-70K		2.00	8.40
200-35-DQ	51-230-70K		2.00	9.00
200-80-DQ	51-476-70K		2.00	18.00
BALSTON	HEADLINE	FINITE	Inside Diameter	Overall Length
DX Grade 95% Efficiency at 0.3 microns				
050-05-DX	12-32-70C		0.50	1.25
050-11-DX	12-57-70C	10H04-013X10	0.50	2.25
100-09-DX	25-51-70C	10H04-023X10	1.00	2.00
100-12-DX	25-64-70C	10H10-020X8	1.00	2.50
100-18-DX	25-127-70C	10H10-025X8	1.00	5.00
100-25-DX	25-178-70C	10H10-050X4	1.00	7.00
150-19-DX	38-152-70C	10H10-070X4	1.50	6.00
200-16-DX	51-89-70C	10H15-060X4	2.00	3.50
200-30-DX	51-213-70C	10H20-035X4	2.00	8.40
200-35-DX	51-230-70C	10H20-090X2	2.00	9.00
200-75-DX	51-460-70C		2.00	18.00
200-80-DX	51-476-70C	10H20-187X1	2.00	18.75

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.



Balston – Headline Equivalent Specifications

These Millennium Filter elements are made of borosilicate glass microfibers with a fluorocarbon resin binder and are resistant to water, hydrocarbon and synthetic lubricants. Element sizes range from 0.5 inch Inside Diameter to 2.0 inch ID. Overall length ranges from 1.25-inches to over 18.0 inches. Filtration efficiency depends on grade level is measured as high as 99.998% efficiency at 0.3 microns.

Grades AAQ / AQ

BALSTON	HEADLINE	Inside Diameter	Overall Length
AAQ Grade 99.998% Efficiency at 0.3 microns			
050-05-AAQ	12-32-30K	0.50	1.25
050-11-AAQ	12-57-30K	0.50	2.25
100-09-AAQ	25-51-30K	1.00	2.00
100-12-AAQ	25-64-30K	1.00	2.50
100-18-AAQ	25-127-30K	1.00	5.00
100-25-AAQ	25-178-30K	1.00	7.00
150-19-AAQ	38-152-30K	1.50	6.00
200-16-AAQ	51-89-30K	2.00	3.50
200-30-AAQ	51-213-30K	2.00	8.40
200-35-AAQ	51-230-30K	2.00	9.00
200-80-AAQ	51-476-30K	2.00	18.00
BALSTON	HEADLINE	Inside Diameter	Overall Length
AQ Grade 99.998% Efficiency at 0.3 microns			
050-05-AQ	12-32-40K	0.50	1.25
050-11-AQ	12-57-40K	0.50	2.25
100-09-AQ	25-51-40K	1.00	2.00
100-12-AQ	25-64-40K	1.00	2.50
100-18-AQ	25-127-40K	1.00	5.00
100-25-AQ	25-178-40K	1.00	7.00
150-19-AQ	38-152-40K	1.50	6.00
200-16-AQ	51-89-40K	2.00	3.50
200-30-AQ	51-213-40K	2.00	8.40
200-35-AQ	51-230-40K	2.00	9.00
200-80-AQ	51-476-40K	2.00	18.00

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.