



Millennium-Filters.com
 QUALITY OEM REPLACEMENT FILTERS



FILTERSOFT-H8913MDVL

| Product Attribute | Specifications |
|------------------------|---|
| Filter Type: | Hydraulic Filter Cartridge |
| Media Type: | Pleated Microglass Media [Avail in Stainless Steel Mesh, Pleated Paper, and Water Removal Media] |
| Overall Height: | 12.91" |
| OD: | 3.79" |
| ID: | 2.20" |
| Collapse Pressure: | 365 PSI (also available in High Collapse version rated up to 3045 PSI) |
| Operating Temperature: | -13° to 250°F |
| Direction of Flow: | Outside-In |
| Seal Material: | Viton |
| Micron Rating: | 10 |
| Beta Ratio: | 200/13 |
| Efficiency: | 99.5% |

| MEDIA Available | Micron Ratings available |
|---|---|
| Pleated Microglass Media + Water Removal Media | 1-micron, 3µm, 6µm, 10µm, 25µm, 40µm 1GW, 3GW, 6GW, 10GW, 25GW, 40GW |
| Pleated Paper Media + Water Removal Media | 3-micron, 6µm, 10µm, 25µm 1PW, 10PW, 25PW |
| Stainless Steel Wire Mesh Media (304 SS) | 10-micron Stainless Steel, 25SS, 40SS, 60SS, 74SS, 100SS, 125SS, 150SS, 200SS, 250SS, 420SS, 500SS |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.