



Millennium-Filters.com
 QUALITY OEM REPLACEMENT FILTERS



HY-PRO-HP170L1012MV

| Product Attribute | Specifications |
|------------------------|---|
| Filter Type: | Hydraulic Filter Cartridge |
| Media Type: | Pleated Microglass (see chart below) |
| Overall Height: | 9.61" |
| OD: | 2.36" |
| ID: | 0.99" |
| Collapse Pressure: | 305 PSI (3045 PSI High Collapse models available) |
| Operating Temperature: | -13° to 250°F |
| Filter Area: | 2.66 SQ.FT. |
| Direction of Flow: | Outside-In |
| Seal Material: | Viton |
| Micron Rating: | 10 (see options below) |
| Beta Ratio: | 200/13 |
| Efficiency: | 99.5% |

| MEDIA Available | Micron Ratings available |
|--|---|
| Pleated Microglass Media GW = Glass + Water Removal Media | 3-micron, 6µm, 10µm, 25µm, 40µm 3GW, 6GW, 10GW, 25GW |
| Pleated Paper Media PW = Paper + Water Removal Media | 3-micron, 10µm, 25µm 10PW, 25PW |
| Stainless Steel Wire Mesh Media (304 SS) | 10-micron, 25µm, 40µm, 74µm, 100µm, 149µm, 250µm |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.