



Millennium-Filters.com  
QUALITY OEM REPLACEMENT FILTERS



## HY-PRO HP66RNL1812MSB

10µm, 3 bar bypass (BPVS)

| Product Attribute         | Specifications             |
|---------------------------|----------------------------|
| Filter Type:              | Hydraulic Filter Cartridge |
| Media Type:               | Pleated Microglass Media   |
| Overall Height:           | 16.22"                     |
| Outer Diameter:           | 4.48"                      |
| Inside Diameter - Bottom: | 2.69"                      |
| BPVS* Setting:            | 3.00 bar                   |
| Collapse Pressure:        | 435 PSI                    |
| Operating Temperature:    | -13° to 250°F              |
| Filter Area:              | 11.84 Square Feet          |
| Direction of Flow:        | OUTSIDE – IN               |
| Seal Material:            | VITON                      |
| Micron Rating:            | 10                         |
| Beta Ratio:               | 200/10                     |
| BPVS* Setting:            | 3.00 bar                   |

\* The standard unit is equipped with an integral bypass valve that is built into the closed end cap allowing fluid to flow when the pressure reaches the set level to avoid system shutdown. Elements should be changed to prevent buildup of contaminants in the system. Bypass valve settings are 1-bar, 3-bar and 6-bar.

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.