



Millennium-Filters.com  
QUALITY OEM REPLACEMENT FILTERS



## HY-PRO-HP66RNL1825WB

25µm, 3 bar bypass (BPVS)

Product Attribute	Specifications
Filter Type:	Hydraulic Return Line Filter Cartridge
Media Type:	304SS Stainless Steel Wire Mesh Media
Overall Height:	16.22"
Outer Diameter:	4.48"
Inside Diameter - Bottom:	2.69"
Collapse Pressure:	305 PSI
Operating Temperature:	-13° to 250°F
Direction of Flow:	OUTSIDE – IN
Seal Material:	VITON
Micron Rating:	25
BPVS* Setting:	3.00 bar [Available with 1-bar or 6-bar bypass]

\* Standard unit is equipped with an integral bypass valve built into the closed end cap allowing fluid to flow when the pressure reaches the set level to avoid system shutdown. Elements should be changed to prevent buildup of contaminants.

Media Available	Micron Ratings available
Pleated Microglass Media [Water Removal Media Available]	3-micron, 5µm, 10µm, 20µm, 40µm
Pleated Paper Media	3-micron, 5µm, 10µm, 20µm
Stainless Steel Wire Mesh Media (304 SS)	10µm, 25µm, 50µm, 60µm, 74µm, 80µm, 100µm, 149µm
Sintered Fiber Media	3-micron, 5µm, 20µm

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.

