



Millennium-Filters.com  
 QUALITY OEM REPLACEMENT FILTERS



**NAPA 7868**

**10µm, Pleated Microglass Media**

| Product Attribute         | Specifications  |
|---------------------------|---|
| Filter Type:              | Hydraulic Filter Cartridge                            |
| Media Type:               | Pleated Microglass Media                              |
| Overall Height:           | 6.02"   |
| Outer Diameter:           | 1.85"   |
| Inside Diameter - Bottom: | 0.87"   |
| Collapse Pressure:        | 435 PSI [Available in High Collapse Version 3045 psi] |
| Operating Temperature:    | -13° to 250°F   |
| Filter Area:              | .95 Square Feet                                       |
| Direction of Flow:        | OUTSIDE – IN  |
| Seal Material:            | VITON   |
| Micron Rating:            | 10  |
| Beta Ratio:               | 200/13  |

| MEDIA Available                             | Micron Ratings available   |
|---|--|
| Pleated Microglass Media                    | 3-micron, 5µm, 10µm, 20µm<br>Water Removal Media Available       |
| Pleated Paper Media                         | 3-micron, 5µm, 10µm, 20µm  |
| Stainless Steel Wire Mesh Media<br>(304 SS) | 10-micron, 25µm, 50µm, 80µm<br>100µm, 125µm, 149µm, 200µm, 250µm |
| Sintered Fiber Media                        | 3-micron Sintered-Fiber, 10-micron SF, 20-micron SF              |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.