



Millennium-Filters.com  
QUALITY OEM REPLACEMENT FILTERS



## SCHROEDER KK10

| Product Attribute      | Specifications             |
|------------------------|----------------------------|
| Filter Type:           | Hydraulic Filter Cartridge |
| Media Type:            | Paper                      |
| Overall Height:        | 18.75"                     |
| OD Top:                | 3.88"                      |
| ID Top:                | 1.61"                      |
| Collapse Pressure:     | 145 psi                    |
| Operating Temperature: | -13°F to 250°F             |
| Direction of Flow:     | Outside > In               |
| Filter Area:           | 14.55 sq.ft.               |
| Seal Material:         | BUNA                       |
| Beta Ratio:            | 2/10                       |
| Micron Rating:         | 10                         |



Millennium-Filters.com  
 QUALITY OEM REPLACEMENT FILTERS



## SCHROEDER KK10

| DIMENSIONS (INCHES)    |                           |                  |                       |      |   |   |   |
|------------------------|---------------------------|------------------|-----------------------|------|---|---|---|
| A                      | B                         | C                | D                     | E    | F | G | H |
| 3.88                   | 1.61                      | 18.75            | 1.61                  | 3.88 |   |   |   |
|                        |                           |                  |                       |      |   |   |   |
| <b>TOL</b>             | <b>±</b>                  |                  |                       |      |   |   |   |
| A                      | 0.012                     |                  |                       |      |   |   |   |
| B                      | 0.008                     |                  |                       |      |   |   |   |
| C                      | 0.098                     |                  |                       |      |   |   |   |
| D                      | 0.008                     |                  |                       |      |   |   |   |
| E                      | 0.012                     |                  |                       |      |   |   |   |
| F                      |                           |                  |                       |      |   |   |   |
| G                      |                           |                  |                       |      |   |   |   |
| H                      |                           |                  |                       |      |   |   |   |
| <b>COLLAPSE RATING</b> | <b>TEMPERATURE RATING</b> | <b>SEAL TYPE</b> | <b>FLOW DIRECTION</b> |      |   |   |   |
| 145 PSI                | -13 F TO 250 F            | BUNA GROMMET     | OUTSIDE-IN            |      |   |   |   |