



SCHROEDER SBF0240DS7V

| Product Attribute | Specifications |
|---------------------------|----------------------------------------------------------|
| Filter Type: | Hydraulic Filter Cartridge |
| Media Type: | Pleated Microglass (Avail in Stainless & Pleated Paper) |
| Overall Height: | 6.81" |
| Outer Diameter: | 2.72" |
| Inside Diameter - Bottom: | 1.33" |
| Collapse Pressure: | 435 PSI (Available with High Collapse Pressure 3045 psi) |
| Operating Temperature: | -13° to 250°F |
| Filter Area: | 307 Square Inches |
| Direction of Flow: | OUTSIDE – IN |
| Seal Material: | VITON |
| Micron Rating: | 10 (Avail from 3-micron to 200 – see chart below) |
| Beta Ratio 1: | 200/9.9 |
| Beta Ratio 2: | 1000/12.4 |

| Media Available | Micron Ratings |
|---------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| Pleated Microglass Media | 3-micron microglass, 5µm, 10µm, 20µm |
| Pleated Paper Media | 3-micron paper media, 10µm |
| Stainless Steel Mesh Media (304 SS) High Efficiency Sintered Fiber also available | 25-micron stainless, 40µm, 50µm, 74µm, 80µm, 100µm, 149µm, 200µm |

Millennium-Filters are Made In America under ISO 9001:2008 Certification. All Millennium-Filter products are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.