



Millennium-Filters.com
 QUALITY OEM REPLACEMENT FILTERS



SWIFT SF060DN612UM 10µm, Pleated Microglass Media

Product Attribute	Specifications
Filter Type:	Hydraulic Filter Cartridge
Media Type:	Pleated Microglass Media
Overall Height:	6.02"
Outer Diameter:	1.85"
Inside Diameter - Bottom:	0.87"
Collapse Pressure:	435 PSI [Available in High Collapse Version 3045 psi]
Operating Temperature:	-13° to 250°F
Filter Area:	.95 Square Feet
Direction of Flow:	OUTSIDE – IN
Seal Material:	VITON
Micron Rating:	10
Beta Ratio:	200/13

MEDIA Available	Micron Ratings available
Pleated Microglass Media	3-micron, 5µm, 10µm, 20µm Water Removal Media Available
Pleated Paper Media	3-micron, 5µm, 10µm, 20µm
Stainless Steel Wire Mesh Media (304 SS)	10-micron, 25µm, 50µm, 80µm 100µm, 125µm, 149µm, 200µm, 250µm
Sintered Fiber Media	3-micron Sintered-Fiber, 10-micron SF, 20-micron SF

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.