



## SWIFT SF160DN725UMV

| Product Attribute         | Specifications   |
|---------------------------|--|
| Filter Type:              | Hydraulic Filter Cartridge                               |
| Media Type:               | Pleated Microglass (Avail in Stainless & Pleated Paper)  |
| Overall Height:           | 6.81"  |
| Outer Diameter:           | 2.72"  |
| Inside Diameter - Bottom: | 1.33"  |
| Collapse Pressure:        | 435 PSI (Available with High Collapse Pressure 3045 psi) |
| Operating Temperature:    | -13° to 250°F  |
| Filter Area:              | 2.12 Square Feet   |
| Direction of Flow:        | OUTSIDE – IN   |
| Seal Material:            | VITON  |
| Micron Rating:            | 20 (Avail from 3-micron to 200 – see chart below)        |
| Beta Ratio:               | 200/20   |

| Media Available   | Micron Ratings   |
|---|--|
| Pleated Microglass Media  | 3-micron microglass, 5µm, 10µm, 20µm                             |
| Pleated Paper Media   | 3-micron paper media, 10µm                                       |
| Stainless Steel Mesh Media (304 SS)<br><b>High Efficiency Sintered Fiber also available</b> | 25-micron stainless, 40µm, 50µm, 74µm, 80µm, 100µm, 149µm, 200µm |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.