

DRP-240-48, DR-120-24, DR-4524, MDR-40-24, MDR-60-24

DIN-Rail Power Supplies



DRP-240-48 DR-120-24 DR-4524 MDR-40-24 MDR-60-24

Features

- ◆ Protections: Short circuit / Overload / Over voltage
- ◆ LED indicator for power on
- ◆ Cooling by free air convection
- ◆ Installation mounting by Din Rail
- ◆ UL508, UL60950-1, TUV, CE approved
- ◆ Heavy industry grade EMS approved
- ◆ 3 years warranty

Specifications

Model Name		DRP-240-48	DR-120-24	DR-4524
Output	Dc Voltage	48V	24V	24V
	Rated Current	5A	5A	2A
	Current Range	0~5A	0 ~ 5A	0 ~ 2A
	Rated Power	240W	120W	48W
	Output Voltage Adj. Range	48~53V	24 ~ 28V	21.6 ~ 26.4V
Input	Voltage Range	85 ~ 264VAC / 120 ~ 370VDC	88 ~ 132VAC / 176 ~ 264VAC, 248 ~ 370VDC by switch	85 ~ 264VAC / 120 ~ 370VDC
	Frequency Range	47 ~ 63Hz	47 ~ 63Hz	47 ~ 63Hz
	Efficiency (Typ.)	85%	84%	80%
Protection	Overload	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed
	Over Voltage	54 ~ 60V Protection type : Shut down o/p voltage, re-power on to recover	29 ~ 33V Protection type : Shut down o/p voltage, re-power on to recover	27.6 ~ 32.4V Protection type : Shut off o/p voltage, clamping by zener diode
Alarm Relay	DC OK Relay			
Indicator	LED	Power On	Power On	Power On
Housing	Dimension	125.5 x 125.2 x 100mm (W x H x D)	65.5 x 125.2 x 100mm (W x H x D)	78 x 93 x 67mm (W x H x D)
	Installation Mounting	DIN Rail	DIN Rail	DIN Rail
Environment	Working Temp.	-10 ~ +70°C	-10 ~ 60°C	-10 ~ 50°C
	Working Humidity	20 ~ 90% RH non-condensing	20 ~ 90% RH non-condensing	20 ~ 90% RH non-condensing
	Storage Temp., Humidity	-20 ~ 85°C, 10 ~ 95% RH	-20 ~ 85°C, 10 ~ 95% RH	-20 ~ 85°C, 10 ~ 95% RH
	Vibration	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6
Safety & EMC	Safety Standards	UL508, UL60950-1, TUV EN60950-1 approved	UL508, UL60950-1, TUV EN60950-1 approved	UL508, TUV EN60950-1 approved
	EMC Emission	Compliance to EN55011, EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2, -3	Compliance to EN55011, EN55022 (CISPR22) Class B, EN61000-3-2,-3	Compliance to EN55011, EN55022 (CISPR22) Class B, EN61000-3-2,-3
	EMC Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2 heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2 (EN50082-2), heavy industry level, criteria A
Others	PFC	Built in Active PFC		Built in Active PFC
	MTBF	289.9K hrs min. MIL-HDBK-217F (25°C)	136.8Khrs min. MIL-HDBK-217F (25°C)	364.6K hrs min. MIL-HDBK-217F (25°C)
	Waranty	3 Years	3 Years	3 Years

Specifications

Model Name		MDR-40-24	MDR-60-24
Output	Dc Voltage	24V	24V
	Rated Current	1.7A	2.5A
	Current Range	0 ~ 1.7A	0~2.5A
	Rated Power	40.8W	60W
	Output Voltage Adj. Range	24 ~ 30V	24~30V
Input	Voltage Range	85 ~ 264VAC / 120 ~ 370VDC	85 ~ 264VAC / 120 ~ 370VDC
	Frequency Range	47 ~ 63Hz	47 ~ 63Hz
	Efficiency (Typ.)	88%	88%
Protection	Overload	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed
	Over Voltage	31.2 ~ 36V Protection type : Shut down o/p voltage, re-power on to recover	31.2 ~ 36V Protection type : Shut down o/p voltage, re-power on to recover
Alarm Relay	DC OK Relay	DC OK Relay will Close In Normal Relay contact rating(max.): 30V/1A resistive	DC OK Relay will Close Relay contact rating(max.): 30V/1A resistive
Indicator	LED	DC OK	Power On
Housing	Dimension	40 x 90 x 100mm (W x H x D)	40 x 90 x 100mm (W x H x D)
	Installation Mounting	DIN Rail	DIN Rail
Environment	Working Temp.	-20 ~ +70°C	-20 ~ 70°C
	Working Humidity	20 ~ 90% RH non-condensing	20 ~ 90% RH non-condensing
	Storage Temp., Humidity	-40 ~ 85°C , 10 ~ 95% RH	-40 ~ 85°C , 10 ~ 95% RH
	Vibration	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6
Safety & EMC	Safety Standards	UL508, UL60950-1, TUV EN60950-1 approved	UL508, UL60950-1, TUV EN60950-1 approved
	EMC Emission	Compliance to EN55011, EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2, -3	Compliance to EN55011, EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2, -3
	EMC Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A
Others	PFC		
	MTBF	301.7K hrs min. MIL-HDBK-217F (25°C)	299.2K hrs min. MIL-HDBK-217F (25°C)
	Waranty	3 Years	3 Years

Ordering Information

Model Name	Description
DRP-240-48	Industrial Power, Input 85~264VAC, Output 48VDC, 240W, -10 ~ +70°C
DR-120-24	Industrial Power, Input 88 ~ 132VAC / 176 ~ 264VAC, Output 24VDC, 120W, -10 ~ +60°C
DR-4524	Industrial Power, Input 85 ~ 264VAC, Output 24VDC, 48W, -10 ~ +50°C
MDR-40-24	Industrial Power, Input 85 ~ 264VAC, Output 24VDC, 40W, -20 ~ +70°C
MDR-60-24	Industrial Power, Input 85~264VAC, Output 24VDC, 60W, -20 ~ +70°C