



Please read instructions carefully before installation. We recommend this product be installed by a qualified, and experienced technician. If you are unsure of any of the below directions and or your ability to correctly and securely install this product, please contact us or your local dealer for help.

Below diagrams show typical installation, your vehicle may be different so please use diagrams as a guide. Make sure your vehicle is clean and free from dirt, road grime etc. where the this product mounts. It is the riders responsibility to make sure the product is mounted and secure before each use. Loading the bag may result in a change of position, always check for proper mounting position after loading and before each and every ride.

Rigg Gear cooler bags are designed with a universal mounting system for Motorcycles, ATV/ UTV, PWC or snowmobile.



Prior to installing your cooler bag, fill with your favorite beverages and ice. Then install the optional shelf by placing on top of contents and onto the self-fastening straps inside the bag. This will help hold your contents in place and keep them from moving inside the cooler over rough terrain.



Position cooler on vehicle making sure the bag is centered and free from moving and hot parts. The bag can be mounted length ways (front to rear) or width ways across (left to right)

Next using the supplied loop straps, pass loop end around a secure part of the vehicle. Then pass the buckle through the loop and pull tight. Repeat with all straps. Connect male buckles to cooler bag. For UTV applications, pass strap around secure location thru holes in the bed, bed tie-downs or "D" rings.

Your cooler bag has a removable /replaceable liner. To remove liner simply pull top seam of liner apart from bag. It is secured with hook and loop self-fastening strips on to the opening of the bag. The liner can be cleaned with mild soap and water, do not use harsh chemicals. The waterproof liner is not warranted for puncture holes or leaking. For replacement liners go to www.nelsonrigg.com .



Warning:

Read the installation instructions and make yourself familiar with the process of installing the Nelson-Rigg® product(s) on your bike. It is your responsibility to mount the product correctly and securely as outlined in these instructions. Nelson-Rigg® products are intended for use at USA street legal speeds as posted by the individual States. Nelson-Rigg® luggage must not be overloaded. Max carrying capacity is 10 lbs per bag or the maximum load suggested by the manufacturer of the vehicle, whichever is less.

Failure to adhere to these warnings may result in, but not be limited to: the luggage becoming detached, the product becoming tangled in moving parts of the vehicle, unstable vehicle dynamics, reduction in the ability to control the vehicle. The result(s) could lead to serious injury.

Always ride safely, adhering to the local highway regulations. Always wear a helmet and protective apparel.

3518-A Lake Center Dr Santa Ana, CA 92704
Tel (714)850-1811 Fax (714)850-1848
e-mail: info@nelsonrigg.com www.nelsonrigg.com

