

# Over Armour Offroad

2515 Bypass Rd. Flemingsburg, KY 41041  
606-845-7439

## Instructions for Installation and Care of Arctic Cat Prowler Soft Door Kit AC-PROWLER-SDK01

**Notice: Cab is Flammable. Do not smoke inside the cab or expose the enclosure to direct flames.**

1. Be sure to read the instructions thoroughly before unrolling and installing the Over Armour Cab Enclosure. For best results installation should be done at temperatures 65\* Fahrenheit and above. Temperatures below 65\* will affect the adhesive Velcro. If installation must be done in colder weather places the adhesive Velcro in a warm area until ready to apply to the vehicle.
2. Carefully unroll the Cab Enclosure on a large, flat, clean surface. Open the hood compartment and raise the bed. This will allow access to the front and rear of the vehicle for necessary installation of Velcro.
3. Check all parts with list shown below:
  - 2" wide Self adhesive Velcro Hook:
    - 45" ----- 4 each
    - 12" ----- 2 each
    - 8" ----- 2 each
    - 6" ----- 2 each
    - 4" ----- 2 each
  - 1" wide Self adhesive Velcro Hook:
    - 24" ----- 2 each
  - Soft Doors ----- 2 each
4. Begin installation by placing the 45" adhesive Velcro strip around the wide outside edge of the front roll bar starting at the front corner and working your way up. You may need to cut the Velcro to fit around your windshield clamps. Be certain to clean the surfaces before applying the adhesive hook strips!
5. Next apply the other 45" strip starting at the rear corner working your way up the frame.
6. Now take the door and line up the front corners and attach the door up the roll cage. Then pull the door to the rear and attach the top part to the velcro making sure the door is properly aligned and straight.

7. Now take the remaining velcro strips and match them up with the pieces sewn to the lower portion of the door.
8. Finally take the strap sewn to the top of the door and run it around the center frame brace to help hold the door in place.

#### Cleaning and Storage Recommendations:

1. Before removing the Over Armour Cab for storage, make sure it is very clean in order to prevent scratching of the window panels. Clean with a soft rag or sponge (I recommend a flannel or Micro Fiber Cloths) using a mild liquid detergent soap and warm water solution. Never rub the windows with a dry cloth or rag! Let the Cab dry thoroughly before attempting to roll for storage.
2. It is important that the Cab be rolled up for storage rather than folding. Folding will cause damage to the windows!!! Carefully roll up the Cab similar to the way it was when it was packed at the factory. On a large, clean and flat surface, fold the doors over the rear panel first, then, interleave the top and windshield on top of the doors. Begin rolling the Cab into a roll approximately 8 inches in diameter. Put the rolled Cab back into the carton for storage at a normal room temperature. It is best not to expose the Cab to either extreme hot or cold temperatures when storing.
3. A special cleaner conditioner is available from Over Armour that will greatly increase the service life of the Cab Enclosure. In addition, if additional hook and loop sets are needed, they can also be ordered.

## Return Policy

If for any reason you choose to return this product it must be returned within **30 days from date item is received**. You **MUST** package the product exactly **as it was originally packaged from the factory to get a full refund for the product!**

The vinyl windows should never be folded when packaging in the box or for storage purposes. Lay all the windows on top of each other with the canvas folded in between and the paper (if available) on both sides of the windows.

**All returned products will be inspected upon arrival at the production facility and must be in unused, factory new condition to receive refund - a 25% restocking fee will apply.**

If ordered from Over Armour Offroad please call at 606-845-7439 to gain a return authorization number, use our preferred shipping carrier (UPS) to return the item (unless the item is defective, you are responsible for paying the shipping to return the item.) **Any returns submitted to Over Armour Offroad without a return authorization number will be charged a 20% restocking fee.** If ordered from one of Over Armour Offroads many distributors', you must first call them and see what their return policy is. Once your item reaches our production facility, our customer satisfaction team will inspect your item to ensure unused, factory new condition. **NOTE: All windshields must be returned with the original protective film intact and not removed. Do NOT REMOVE if you have any intentions of returning the item. Refund/ replacement of a windshield will only be processed on items with original protective film or if the windshield is defective.**

Items must be properly packaged in the original shipping carton to protect them during transit and ensure your returned item arrives back factory fresh, and in new resalable condition (**any returned items that have been used, altered or damaged in any way will not be subject for a refund.**) All contents including instruction manuals, accessories, hardware, Velcro, etc. must be included in your return shipment. Only items in OEM factory new condition will be approved. Once returned items are received, credit will be issued to the original credit card/ payment method used for the purchase. Outbound shipping and return shipping cost will not be refunded. Please allow 4 to 6 weeks for your refund to be processed.

## Warranty

To The Owner of this Product:

Thank you for purchasing one of Over Armour Offroad Cab Enclosures, Tops &/or Windshields! Below are the terms under which your product is covered under our manufacturer's warranty.

30 Day Warranty which includes and is not limited to replacing the enclosure, tops and/or windshield due to defect of the product. Please refer to the return policy in this case for more information.

1 Year Warranty includes any defect in material or workmanship within this time frame we will gladly correct the problem or replace the enclosure, tops &/or windshield. Upon submitting for the correction or replacement we will need to receive pictures of the defect in material or workmanship along with the receipt from the date of purchase.

Thank you,

Over Armour Offroad

[www.overarmouroffroad.com](http://www.overarmouroffroad.com)