

Over Armour Offroad

2515 Bypass Rd. Flemingsburg, KY 41041
606-845-7439

Instructions for Installation and Care of
Honda Big Red
Mini Cab Enclosure
HO-BIGRED-MC01

CAUTION: Do not smoke inside the cab or expose the product to direct flames. Product is FLAMMABLE.

Be sure to read these instructions thoroughly before opening and installing the product. The installation is best done when the temperature is 70°F or warmer. The temperature affects the adhesive Velcro. If conditions prevent installing in warmer weather it helps to store the adhesive Velcro at room temperature prior to installation.

1. Carefully open the carton and remove the roll the product out on a large flat surface that is clean and free of dirt. The presence of dirt may cause soiling to the textile and scratch the clear vinyl window.

2. Check over the parts included in the carton with the parts list shown below:

Velcro hook strips	2 each	18" long
Velcro hook strips	2 each	10" long
Velcro hook strips	4 each	5" long
Screw Snaps	5 each	
Mini Cab	1 each	

3. With assistance, begin by draping the enclosure over the top of the roll cage and center it. Pull the three straps sewn to the front nose down and wrap them around the front bumper as shown in the photo below. Run the straps back through the buckle but do not tighten them down yet.



4. Now move around to the rear of the cab and with the bed raised mark the locations for the four screw studs to match up with the snaps installed into the cab enclosure. Using a #2 Phillips screwdriver install the screw snaps into the plastic. TIP: You may wish to install the snaps slightly below what it looks like to ensure a tight fit, or just be sure to pull down on the cab as you mark the locations.
5. Now place the remaining Velcro to the roll cage on either side of the windshield, matching up the adhesive Velcro with the tabs sewn into the enclosure. Pull the windshield tight from side to side.
6. Then attach the 5” adhesive strips down the sides of the rear window to match up with the tabs sewn to the cab.
7. Finally, pull the straps tight on the nose to complete installation.

Cleaning and Storage Recommendations:

1. Before removing the product for storage, make sure it is clean and dry, to prevent soiling the textile and scratching the clear vinyl rear window. Clean with a soft rag or sponge using a mild liquid detergent soap and warm water solution. Let the product dry thoroughly before attempting to roll for storage.
2. It is important that the cab be rolled up for storage rather than folding. Folding will cause undesirable creasing of both the textile and the clear vinyl rear window. Carefully roll up the product similar to the way it was when it was packed at the factory. Put the rolled product back into the carton for storage at a normal room temperature. It is best not to expose the product to either extreme hot or cold temperatures when storing.
3. A special cleaner/conditioner is available from Over Armour Offroad that will greatly increase the service life of the product. If needed, additional hook and loop sets are available, as well as other spare parts and hardware. Contact Over Armour Offroad for information.
4. Transporting or trailering your UTV with the product installed is not generally recommended. It is best to remove the product before transporting your UTV.

Return Policy

Over Armour Offroad

2515 Bypass Rd, Flemingsburg, KY 41041
Phone: 606-845-7439

If for any reason you choose to return this product it must be returned within **30 days from date item is received**. You **MUST** package the product exactly as it was **originally packaged from the factory to get a full refund for the product!**

The vinyl windows should never be folded when packaging in the box or for storage purposes. Lay all the windows on top of each other with the canvas folded in between and the paper (if available) on both sides of the windows.

All returned products will be inspected upon arrival at the production facility and must be in unused, factory new condition to receive refund - a 20% restocking fee will apply.

If ordered from Over Armour Offroad please call at 606-845-7439 to gain a return authorization number, use our preferred shipping carrier (UPS) to return the item (unless the item is defective, you are responsible for paying the shipping to return the item.) **Any returns submitted to Over Armour Offroad without a return authorization number will be charged a 20% restocking fee.** If ordered from one of Over Armour Offroads many distributors', you must first call them and see what their return policy is. Once your item reaches our production facility, our customer satisfaction team will inspect your item to ensure unused, factory new condition. **NOTE: All windshields must be returned with the original protective film intact and not removed. Do NOT REMOVE if you have any intentions of returning the item. Refund/ replacement of a windshield will only be processed on items with original protective film or if the windshield is defective.**

Items must be properly packaged in the original shipping carton to protect them during transit and ensure your returned item arrives back factory fresh, and in new resalable condition (**any returned items that have been used, altered or damaged in any way will not be subject for a refund.**) All contents including instruction manuals, accessories, hardware, Velcro, etc. must be included in your return shipment. Only items in OEM factory new condition will be approved. Once returned items are received, credit will be issued to the original credit card/ payment method used for the purchase. Outbound shipping and return shipping cost will not be refunded. Please allow 4 to 6 weeks for your refund to be processed.

Warranty
Over Armour Offroad
2515 Bypass Rd, Flemingsburg, KY 41041
Phone: 606-845-7439

To The Owner of this Product:

Thank you for purchasing one of Over Armour Offroad Cab Enclosures &/or Windshields! Below are the terms under which your product is covered under our manufacturer's warranty.

30 Day Warranty which includes and is not limited to replacing the enclosure and/or windshield due to defect of the product. Please refer to the return policy in this case for more information.

1 Year Warranty includes any defect in material or workmanship within this time frame we will gladly correct the problem or replace the enclosure &/or windshield. Upon submitting for the correction or replacement we will need to receive pictures of the defect in material or workmanship along with the receipt from the date of purchase.

Thank you,

Darren Royse
Owner/Operator
www.overarmouroffroad.com