

Over Armour Offroad

2515 Bypass Rd. Flemingsburg, KY 41041
606-845-7439

Instructions for Installation and Care of Kawasaki 610 Mule Rear Window Enclosure

CAUTION: Do not smoke inside the cab or expose the enclosure to direct flames.
Product is FLAMMABLE.

Be sure to read these instructions thoroughly before opening and installing the enclosure. The installation is best done when the temperature is 60°F or warmer. Carefully open the carton and unroll the enclosure on a large flat surface that is clean and free of dirt or other material.

Check over the parts included in the carton with the parts list shown below:

Velcro hook strips	10 each	3" long
Velcro hook strips	1 each	25" long
Cab Enclosure	1 each	

1. You must remove the top(if installed) before beginning installation of the Rear Window enclosure. Also, raise the bed of the vehicle.
2. Begin by placing the 25" adhesive Velcro strip across the top of the rear roll bar facing the front of the vehicle(see fig.1). With assistance, slide the enclosure between the cage and the bed and attach the 25" Velcro tab sewn to the top of the rear window to the adhesive strip you just installed. You may need to adjust this later to make sure the cab is centered on the roll cage.



Fig.1

3. Now pull the enclosure down between the rear of the roll cage and the bed(raise the bed prior to performing this step). Apply the 20" adhesive Velcro strip across

the chassis at this location, and attach the corresponding sewn-on Velcro tab at the bottom of the enclosure to it. See fig. 2 below.



Fig.2

4. Next you will work your way to the sides of the enclosure. Starting at the top you will see two double-sided Velcro straps sewn to the corners of the enclosure. At these points you will take the 6" adhesive Velcro strip and wrap them around the bar at the corner, and then wrap the double-sided strip around that to provide a secure grip. There are two more at the bottom; attach the other two 6" strips and attach the double-sided Velcro straps in a similar fashion at these locations. See fig.3.



Fig.3

5. Now you will see two 10" Velcro tabs sewn down the sides of the enclosure. Apply the remaining 10" adhesive Velcro strips to the roll cage on both sides at these locations and attach the sewn-in Velcro tabs. See fig. 4.



Fig.4

Cleaning and Storage Recommendations:

1. Before removing the enclosure for storage, make sure it is clean and dry, to prevent soiling the textile and scratching the clear vinyl side/rear windows. Clean with a soft rag or sponge using a mild liquid detergent soap and warm water solution. Let the enclosure dry thoroughly before attempting to roll for storage.
2. It is important that the enclosure be rolled up for storage rather than folding. Folding will cause undesirable creasing of both the enclosure textile and the clear vinyl side/rear windows. Carefully roll up the enclosure similar to the way it was when it was packed at the factory. Put the rolled enclosure back into the carton for storage at a normal room temperature. It is best not to expose the enclosure to either extreme hot or cold temperatures when storing.
3. A special cleaner/conditioner is available from Mammoth Designs that will greatly increase the service life of the cab enclosure. If needed, additional hook and loop sets are available, as well as other spare parts and hardware. Contact Mammoth Designs for information.
4. Transporting or trailering your UTV with the enclosure installed is not generally recommended. It is best to remove the enclosure before transporting your UTV.

Thank you for your purchase!

**Over Armour Offroad
2515 Bypass Rd, Flemingsburg, KY 41041**

Phone: 606-845-7439 or 606-748-5136

If for any reason you choose to return this product it must be returned within **30 days from date item is received**. You **MUST** package the product exactly as it was originally packaged from the factory to get a full refund for the product!

The vinyl windows should never be folded when packaging in the box or for storage purposes. Lay all the windows on top of each other with the canvas folded in between and the paper (if available) on both sides of the windows. **All returned products will be inspected upon arrival at the production facility and must be in unused, factory new condition to receive refund - a 20% restocking fee will apply.**

If ordered from Over Armour Offroad please call at 606-845-7439 to gain a return authorization number, use our preferred shipping carrier (UPS) to return the item (unless the item is defective, you are responsible for paying the shipping to return the item.) **Any returns submitted to Over Armour Offroad without a return authorization number will be charged a 20% restocking fee.** If ordered from one of Mammoth Designs many distributors', you must first call them and see what their return policy is. Once your item reaches our production facility, our customer satisfaction team will inspect your item to ensure unused, factory new condition. **NOTE: All Lexan windshields must be returned with the original protective film intact and not removed. Do NOT REMOVE if you have any intentions of returning the item. Refund/ replacement on lexan windshields will only be processed on items with original protective film or if the windshield is defective.**

Items must be properly packaged in the original shipping carton to protect them during transit and ensure your returned item arrives back factory fresh, and in new resalable condition (**any returned items that have been used, altered or damaged in any way will not be subject for a refund.**) All contents including instruction manuals, accessories, hardware, Velcro, etc. must be included in your return shipment. Only items in OEM factory new condition will be approved. Once returned items are received, credit will be issued to the original credit card/ payment method used for the purchase. Outbound shipping and return shipping cost will not be refunded. Please allow 4 to 6 weeks for your refund to be processed.



To The Owner of this Product:

Thank you for purchasing one of Over Armour Offroads Enclosure &/or Windshields!
Below are the terms under which your product is covered under our manufacturer's warranty.

30 Day Warranty which includes and is not limited to replacing the enclosure and/or windshield due to defect of the product. Please refer to the return policy in this case for more information.

1 Year Warranty includes any defect in material or workmanship within this time frame we will gladly correct the problem or replace the enclosure &/or windshield. Upon submitting for the correction or replacement we will need to receive pictures of the defect in material or workmanship along with the receipt from the date of purchase.

Thank you

Alyson Rapp

Chief Operations Officer

www.overarmouroffroad.com

606-845-7439