

OVER ARMOUR OFFROAD

2515 Bypass Road Flemingsburg, KY 41041
606-845-7439

Instructions for Installation of 08 and 09 Polaris Ranger Crew **Folding Lexan Windshield** **PO-08&09CREW-WD03**

1. Be sure to read these instructions thoroughly before opening and installing the Polaris Ranger Lexan Windshield.
2. Check over the parts included in the carton with the parts list shown below:

1 ¾" Loom Clamps	6 each
1" Bolts	18 each
Washers	36 each
Lock Nuts	18 each
Rubber Gasket	1 each
4" Adhesive Velcro	4 each
Lexan Plates	2 each
Webbing Straps	2 each
Bent Lexan Brace	1 each
Lexan Windshield	1 each

3. Begin by removing the entire windshield assembly and lay it flat on a clean surface. Get the included rubber gasket and install it along the bottom curved part of the small windshield section. Peel back the protective film along to expose the material. Starting at one end press the gasket firmly along the bottom edge, making sure that it is pushed all the way on. If it does not seem to be holding strong, you can squeeze the gasket together and reinstall to get a better hold.
4. Next take the two small Lexan plates that are rounded on one end and the two webbing straps with Velcro and bolt them to the end of the small section. Bolt them together in the following order from outside to inside: Bolt, Washer, Plate, Webbing, Windshield, Washer, and Lock Nut. Make sure the plate and webbing are on the side of the windshield that does not have the groove in it
5. Now take the bent Lexan brace and install it on the large section of the windshield. Peel off the protective film from both pieces and get 4 bolts, 4 lock nuts and 8 washers out. The brace should go on the inside of the windshield with the bend above the bolts. To help understand which side of the windshield is up; the grooved end is the bottom. The brace is installed from outside in this order; Bolt, Washer, Windshield, Brace, Washer, and Lock Nut.

6. Lay the large windshield section on a table or clean surface and attach the small section to it. Line the up and get the end started for about 10-15 inches and flip the bottom section over on the large one; this should allow you to push the hinge on easier.
7. Next place the windshield on the Ranger, setting it up under the top and on the roll cage. To make the rest of the installation easier get someone to hold the windshield in place by pushing of the front of it while you install the adhesive Velcro strips to the roll cage. Where the strap meets the roll cage wrap the adhesive Velcro strips around the bar starting under the windshield and wrapping it towards the inside of the UTV and around towards the rear. Wrap the straps around the Velcro and this should hold the windshield in place while you install the clamps.
8. Where the slots are cut into the windshield wrap a clamp around the roll cage and insert a bolt through both holes from the inside out. Place a washer on the bolt before putting the bolt through the windshield, then place another washer over the bolt on the outside of the windshield and finally screw the thumb nut on the bolt and tighten. You may need a Phillips screwdriver the hold the bolt while tightening the thumb nut.
9. After tightening down all of the clamps raise the lower sections and mark where the Velcro webbing straps meet up with it and wrap the adhesive Velcro in the same way as before but start it just inside the windshield because you can't raise it up and put in underneath as before.
10. A plastic cleaner and polish is available from Mammoth Designs that will help reduce dust buildup and fingerprints. Just give us a call at 606-845-2227, Thanks.



Return Policy

If for any reason you choose to return this product it must be returned within **30 days from date item is received**. You **MUST** package the product exactly **as it was originally packaged from the factory to get a full refund for the product!**

The vinyl windows should never be folded when packaging in the box or for storage purposes. Lay all the windows on top of each other with the canvas folded in between and the paper (if available) on both sides of the windows.

All returned products will be inspected upon arrival at the production facility and must be in unused, factory new condition to receive refund - a 25% restocking fee will apply.

If ordered from Over Armour Offroad please call at 606-845-7439 to gain a return authorization number, use our preferred shipping carrier (UPS) to return the item (unless the item is defective, you are responsible for paying the shipping to return the item.) **Any returns submitted to Over Armour Offroad without a return authorization number will be charged a 20% restocking fee.** If ordered from one of Over Armour Offroads many distributors', you must first call them and see what their return policy is. Once your item reaches our production facility, our customer satisfaction team will inspect your item to ensure unused, factory new condition. **NOTE: All windshields must be returned with the original protective film intact and not removed. Do NOT REMOVE if you have any intentions of returning the item. Refund/ replacement of a windshield will only be processed on items with original protective film or if the windshield is defective.**

Items must be properly packaged in the original shipping carton to protect them during transit and ensure your returned item arrives back factory fresh, and in new resalable condition (**any returned items that have been used, altered or damaged in any way will not be subject for a refund.**) All contents including instruction manuals, accessories, hardware, Velcro, etc. must be included in your return shipment. Only items in OEM factory new condition will be approved. Once returned items are received, credit will be issued to the original credit card/ payment method used for the purchase. Outbound shipping and return shipping cost will not be refunded. Please allow 4 to 6 weeks for your refund to be processed.

Warranty

To The Owner of this Product:

Thank you for purchasing one of Over Armour Offroad Cab Enclosures, Tops &/or Windshields!
Below are the terms under which your product is covered under our manufacturer's warranty.

30 Day Warranty which includes and is not limited to replacing the enclosure, tops and/or windshield due to defect of the product. Please refer to the return policy in this case for more information.

1 Year Warranty includes any defect in material or workmanship within this time frame we will gladly correct the problem or replace the enclosure, tops &/or windshield. Upon submitting for the correction or replacement we will need to receive pictures of the defect in material or workmanship along with the receipt from the date of purchase.

Thank you,

Over Armour Offroad
www.overarmouroffroad.com