

1. Product and Company Identification

Product identifier	Sonax PROFILINE PolymerNetShield
Other means of identification	02230000-745
Synonyms	Not available.
Recommended use	Car Care
Recommended restrictions	Take precautionary measures against static discharge.
Manufacturer information	Sonax GmbH Münchener Strasse 75 D-86633 Neuburg/Donau DE
Supplier	Vision Investments, LLC 4565 W. 16th Street Indianapolis, IN 46222 US Email: info@sonaxusa.com Phone: 1-317-295-7056

2. Hazards Identification

Physical hazards	Gases under pressure	Liquefied gas
Health hazards	Not classified.	
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word	Warning
Hazard statement	Contains gas under pressure; may explode if heated.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Protect from sunlight. Store in a well-ventilated place.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	5 - 10 *
Distillates (petroleum), light hydrotreated		64742-47-8	0.5 - 1.5 *
Naphtha (petroleum), hydrotreated heavy		64742-48-9	1 - 5 *

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	5 - 10 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. If breathing has stopped, trained personnel should administer CPR immediately.
Skin contact	Do not peel polymer from the skin. Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Do not induce vomiting. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Do not puncture or incinerate container. Do not store at temperatures above 49°C. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wear rubber gloves and safety glasses with side shields. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Treat for surrounding material.
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	Contents under pressure. Cool containers with flooding quantities of water until well after fire is out. Firefighters should wear a self-contained breathing apparatus.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self-contained breathing apparatus.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Before attempting clean up, refer to hazard data given above. Although the chance of a significant spill or leak is unlikely in aerosol containers, in the event of such an occurrence, absorb spilled material with a non-flammable absorbent such as sand or vermiculite. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling	<p>Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not re-use empty containers. Use only with adequate ventilation. Avoid prolonged exposure.</p> <p>Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use good industrial hygiene practices in handling this material.</p>
Conditions for safe storage, including any incompatibilities	<p>Contents under pressure. Do not puncture, incinerate or crush. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.</p>

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Butane (CAS 106-97-8)	TWA	1000 ppm	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m ³	Vapor.
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	1590 mg/m ³	
		400 ppm	
Propane (CAS 74-98-6)	TWA	1000 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Butane (CAS 106-97-8)	STEL	750 ppm	
	TWA	600 ppm	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m ³	Non-aerosol.
Propane (CAS 74-98-6)	TWA	1000 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	800 ppm
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	525 mg/m ³
Propane (CAS 74-98-6)	TWA	1000 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m ³ 800 ppm
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	1590 mg/m ³ 400 ppm
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	1590 mg/m ³

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Propane (CAS 74-98-6)	TWA	400 ppm
		1800 mg/m3
		1000 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	PEL	400 mg/m3
		100 ppm
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3
		100 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	100 mg/m3
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	400 mg/m3
		100 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines See above

Canada - Alberta OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

Appropriate engineering controls Use only under good ventilation conditions or with respiratory protection.

Individual protection measures, such as personal protective equipment

Eye/face protection Not normally required when used as directed.

Skin protection

Hand protection Not normally required when used as directed.

Other As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Thermal hazards Not available.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance Foamy Spray

Physical state Liquid.

Form	Aerosol
Color	White
Odor	Characteristic
Odor threshold	Not available.
pH	7 - 7.5 (active ingredient data)
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 - 527 °F (100 - 275 °C) (active ingredient data)
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.99 - 1.01 g/cm ³ (active ingredient data)
Flammability class	Not Flammable via flame projection testing.

10. Stability and Reactivity

Reactivity	May react with incompatible materials.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Do not pierce or burn after use. Aerosol containers are unstable at temperatures above 49°C (120.2°F). Contact with incompatible materials.
Incompatible materials	Acids. Oxidizers.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.
Information on likely routes of exposure	
Ingestion	Exposure by ingestion of an aerosol is unlikely. May cause stomach distress, nausea or vomiting.
Inhalation	Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).
Skin contact	The finished product is not expected to cause irritation.
Eye contact	The finished product is not expected to cause irritation. Direct contact with eyes may result in mechanical irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 680 mg/L, 2 Hours, HSDB 57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 800000 ppm, 10 Minutes, ECHA 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 276000 ppm, 4 Hours, CCOHS 1443 mg/L, 10 Minutes, ECHA 1355 mg/L, 10 Minutes
<i>Oral</i>		
LD50	Not available	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 4000 mg/kg, 24 Hours, ECHA > 2000 mg/kg > 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Cat	> 6.4 mg/L, 6 Hours, ECHA
	Rat	> 7.5 mg/L, 6 Hours, ECHA > 6 mg/L, 4 Hours, ECHA > 5.7 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA > 4.6 mg/L, 4 Hours, ECHA > 4.5 mg/L, 4 Hours, ECHA > 4.3 mg/L, 4 Hours, ECHA > 0.1 mg/L, 8 Hours, ECHA 5.2 mg/l/4h, LOLI
<i>Oral</i>		
LD50	Rat	> 20000 mg/kg, ECHA > 5000 mg/kg, LOLI > 25 ml/kg

Components	Species	Test Results
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 6000 mg/kg, 24 Hours, ECHA > 3750 mg/kg, 24 Hours, ECHA > 3000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, ECHA > 2000 mg/kg, 24 Hours, ECHA > 1900 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 8530 mg/m3, 4 Hours, ECHA > 7970 mg/m3, 4 Hours, ECHA > 7630 mg/m3, 4 Hours, ECHA > 7300 mg/m3, 4 Hours, ECHA > 5830 mg/m3, 4 Hours, ECHA > 5740 mg/m3, 4 Hours, ECHA > 5610 mg/m3, 4 Hours, ECHA > 5470 mg/m3, 4 Hours, ECHA > 5300 mg/m3, 4 Hours, ECHA > 5280 mg/m3, 4 Hours, ECHA > 5260 mg/m3, 4 Hours, ECHA > 5250 mg/m3, 4 Hours, ECHA > 5240 mg/m3, 4 Hours, ECHA > 5220 mg/m3, 4 Hours, ECHA > 5200 mg/m3, 4 Hours, ECHA > 5170 mg/m3, 4 Hours, ECHA > 5160 mg/m3, 4 Hours, ECHA > 5100 mg/m3, 4 Hours, ECHA > 5080 mg/m3, 4 Hours, ECHA > 5050 mg/m3, 4 Hours, ECHA > 5040 mg/m3, 4 Hours, ECHA > 5020 mg/m3, 4 Hours, ECHA > 5000 mg/m3, 4 Hours, ECHA > 4980 mg/m3, 4 Hours, ECHA > 4970 mg/m3, 4 Hours, ECHA > 4420 mg/m3, 4 Hours, ECHA > 5.4 mg/L, 4 Hours, ECHA > 5.1 mg/L, 4 Hours, ECHA > 5.1 mg/L, 4 Hours, ECHA > 5 mg/L, 4 Hours, ECHA > 5 mg/L, 4 Hours, ECHA >= 5060 mg/m3, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 7000 mg/kg, ECHA > 6000 mg/kg, ECHA > 5570 mg/kg, ECHA > 5200 mg/kg, ECHA > 5000 mg/kg, ECHA > 4800 mg/kg, ECHA

Components	Species	Test Results
		> 4500 mg/kg, ECHA
		> 25 ml/kg, HSDB
		14063 mg/kg, ECHA
		6620 mg/kg, ECHA
		5800 mg/kg, ECHA
		5390 mg/kg, ECHA
		4820 mg/kg, ECHA
Propane (CAS 74-98-6)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 12000000 ppm, 4 hours > 800000 ppm, 10 Minutes, ECHA > 1464 mg/L, 15 Minutes, HSDB 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 1355 mg/L, 10 Minutes
<i>Oral</i>		
LD50	Not available	
Skin corrosion/irritation	Not expected to be a primary skin irritant.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	Not classified.	
Carcinogenicity	Not classified or listed by IARC, NTP, OSHA and ACGIH. Contains < 3% (w/w) DMSO-extract	
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
	Not listed.	
Reproductive toxicity	Not classified.	
Teratogenicity	Not classified.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	

Aspiration hazard	Not classified.
Chronic effects	Non-hazardous by WHMIS/OSHA criteria.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components	Species	Test Results
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
Aquatic		
Crustacea	EC50 Water flea (<i>Daphnia pulex</i>)	2.7 - 5.1 mg/L, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	2.9 mg/L, 96 hours
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Aquatic		
Crustacea	EC50 Water flea (<i>Daphnia pulex</i>)	2.7 - 5.1 mg/L, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	8.8 mg/L, 96 hours
		8.8 mg/L, 96 hours
Persistence and degradability	Not inherently biodegradable.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Mobility in general	Not available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal Considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	Aerosols, non-flammable
Hazard class	2.2

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	U1950
Proper shipping name	AEROSOLS, non-flammable
Hazard class	2.2
Special provisions	80, 107

DOT



TDG



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada DSL Challenge Substances: Listed substance

Butane (CAS 106-97-8) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/identification Number

Butane (CAS 106-97-8) 1 TONNES

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) 1 TONNES

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) 1 TONNES

Propane (CAS 74-98-6) 1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Controlled

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8) Listed.

Propane (CAS 74-98-6) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US state regulations

See below

US - California Hazardous Substances (Director's): Listed substance

Butane (CAS 106-97-8) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

US - Illinois Chemical Safety Act: Listed substance

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US - Louisiana Spill Reporting: Listed substance

Butane (CAS 106-97-8) Listed.

Propane (CAS 74-98-6) Listed.

US - Minnesota Haz Subs: Listed substance

Butane (CAS 106-97-8) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

Propane (CAS 74-98-6) Listed.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Propane (CAS 74-98-6)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Propane (CAS 74-98-6)

US - Texas Effects Screening Levels: Listed substance

Butane (CAS 106-97-8) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

Propane (CAS 74-98-6) Listed.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region

United States & Puerto Rico

Inventory name

Toxic Substances Control Act (TSCA) Inventory

On inventory (yes/no)*


Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		1
PERSONAL PROTECTION		X

**Disclaimer**

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

22-August-2018

Version #

02

Effective date

22-August-2018

Prepared by

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.