

1. Product and Company Identification

Product identifier	SONAX PROFILINE Final
Other means of identification	02783000
Synonyms	Not available.
Recommended use	Polish, Wax, Sealant
Recommended restrictions	None known.
Manufacturer information	Sonax GmbH Münchener Strasse 75 D-86633 Neuburg/Donau DE Phone: 0049 84 31 53-0 24-Hour-Number: GBK/Infotrac ID 91785: . (USA domestic) 1 800 535 5053
Supplier	Vision Investments, LLC 4565 W. 16th Street Indianapolis, IN 46222 US Email: info@sonaxusa.com Phone: 1-317-295-7056

2. Hazards Identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
WHMIS 2015 defined hazards	Not classified
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated middle		64742-46-7	5 - 10 *
Distillates (petroleum), light hydrotreated		64742-47-8	1 - 5 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments	Non-hazardous by WHMIS/OSHA criteria *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret. US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
-----------------------------	--

4. First Aid Measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

5. Fire Fighting Measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide.
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	None known.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling	Avoid prolonged exposure. Use care in handling/storage. When using, do not eat, drink or smoke.
Conditions for safe storage, including any incompatibilities	Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Vapor.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	1 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	1590 mg/m3	
		400 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	PEL	5 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	PEL	400 mg/m3	
		100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	100 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines**Canada - Alberta OELs: Skin designation**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Ethanol, 2-phenoxy- (CAS 122-99-6)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Can be absorbed through the skin.

Appropriate engineering controls Ensure adequate ventilation.**Individual protection measures, such as personal protective equipment****Eye/face protection** Safety glasses recommended.**Skin protection****Hand protection** Rubber gloves. Confirm with a reputable supplier first.**Other** Wear suitable protective clothing.**Respiratory protection** Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).**Thermal hazards** Not applicable.**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke.

9. Physical and Chemical Properties

Appearance	Emulsion
Physical state	Liquid.
Form	Liquid.
Color	Yellow
Odor	Characteristic
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 - 536 °F (100 - 280 °C)
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	152.6 °F (67.0 °C) Sustained combustibility test ISO 9038: No self sustained combustion.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	0.6 % v/v
Explosive limit - upper (%)	7 % v/v
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.95 - 0.96 g/cm ³ @ 20°C
Kinematic viscosity	> 20.5 mm ² /s @ 40°C

10. Stability and Reactivity

Reactivity May react with incompatible materials.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	May cause respiratory tract irritation.
Skin contact	Prolonged skin contact may cause skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.
Direct contact with skin may cause irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA 2000 mg/kg, Madison Chemical
<i>Inhalation</i>		
LC50	Rat	73680 mg/L, 4 Hours, HSDB 7640 mg/m ³ , 4 h, ECHA 7640 mg/m ³ , 4 Hours, ECHA 61 mg/L, 4 Hours, HSDB 4.6 mg/L, 4 Hours, ECHA 1.8 mg/L, 4 Hours, ECHA 1.8 mg/L, 4 Hours, ECHA 1.7 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA > 25 ml/kg, HSDB 7400 mg/kg, LOLI
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 4000 mg/kg, 24 Hours, ECHA > 2000 mg/kg > 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Cat	> 6.4 mg/L, 6 Hours, ECHA
	Rat	> 7.5 mg/L, 6 Hours, ECHA > 6 mg/L, 4 Hours, ECHA > 5.7 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA

Components	Species	Test Results
		> 4.6 mg/L, 4 Hours, ECHA > 4.5 mg/L, 4 Hours, ECHA > 4.3 mg/L, 4 Hours, ECHA > 0.1 mg/L, 8 Hours, ECHA 5.2 mg/l/4h, LOLI
<i>Oral</i> LD50	Rat	> 20000 mg/kg, ECHA > 5000 mg/kg, LOLI > 25 ml/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classified.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	Volume 33, Supplement 7 - 3	Not classifiable as to carcinogenicity to humans.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Teratogenicity	Not available.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not classified.	
Chronic effects	Not classified.	

12. Ecological Information

Ecotoxicity	See below		
Ecotoxicological data			
Components	Species		Test Results
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>)	2.7 - 5.1 mg/L, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	2.9 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Mobility in general	Not available.		

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Kaolin (CAS 1332-58-7) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) 1 TONNES

Canada Priority Substances List (Second List): Listed substance

Kaolin (CAS 1332-58-7) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not controlled

US federal regulations This product is NOT known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethanol, 2-phenoxy- (CAS 122-99-6) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethanol, 2-phenoxy- (CAS 122-99-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

See below

US - California Hazardous Substances (Director's): Listed substance

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

US - Illinois Chemical Safety Act: Listed substance

Ethanol, 2-phenoxy- (CAS 122-99-6)

US - Louisiana Spill Reporting: Listed substance

Ethanol, 2-phenoxy- (CAS 122-99-6) Listed.

US - Minnesota Haz Subs: Listed substance

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Kaolin (CAS 1332-58-7) Listed.

US - New Jersey RTK - Substances: Listed substance

Ethanol, 2-phenoxy- (CAS 122-99-6)

Kaolin (CAS 1332-58-7)

US - Texas Effects Screening Levels: Listed substance

Alkanes, C9- 12-iso- (CAS 90622-57-4) Listed.

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Ethanol, 2-phenoxy- (CAS 122-99-6) Listed.

Kaolin (CAS 1332-58-7) Listed.

Siloxanes and Silicones, dimethyl- (CAS 63148-62-9) Listed.

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Kaolin (CAS 1332-58-7)

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Ethanol, 2-phenoxy- (CAS 122-99-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Ethanol, 2-phenoxy- (CAS 122-99-6)

Kaolin (CAS 1332-58-7)

US. Rhode Island RTK

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Kaolin (CAS 1332-58-7)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 0
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

06-February-2019

Version

02

Effective date

09-November-2018

Prepared by

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.