

The T2100 Series of emergency telephones are designed to withstand the rigors of harsh weather and environments, with electronics sealed with a Mil-Spec protective coating and protected speaker and microphone openings. They can be connected to analog telephone lines from any CO, PBX or Key systems, or integrated into VOIP systems through a VOIP gateway.



T2100



T2110



T2120



T2100C

Key Features:

- Flush mount
- True Talk™ Full Duplex Speaker Phone
- FCC registered
- Built in four number dialer
- Two visual call progress indicators
- Automatic number identifier
- Tone feature for patron signaling
- Two programmable auxiliary outputs
- Remotely programmable
- One or two programmable messages
- Programmable ring count
- Phone line monitoring available



Phone Enclosures Available

Specifications:

- **Dimensions:** 11.75" H x 8.5" W x 2.7" D
- **Weight:** 6 lbs.
- **Material:** 12 ga (0.012") brushed stainless steel
- **Power:** 12-24V isolated DC, or powered from 110VAC converter provided
- **Talk Battery:** 24-56VDC
- **Current Range:** 11-120mA
- **REN:** 1.1
- **Dialing:** Tone or pulse
- **Frequency Response:** 300-3,000Hz
- **Operating Temperature:** -4° to 140° F (-20° to 60° C), 23° to 122° F (-5° to 50° C) (T2100C only)
- **Regulatory Standards**
 - **FCC Reg No:** 5CDUSA-30708-AL-E
 - **Industry Canada No:** 26817738A