



# iS2LX Multimedia Display Installation Guide

## Items Required for Installation

- + Screen
- + Lens
- + Power Supply
- + Cable\*
- + Processor\*\*
- + Processor Power Supply\*\*

\* Required only if display screen is Open Frame.

\*\* If master and open frame installation, then the additional processor and power supply will not be required.

## Mounting Instructions (Display Panel and Power Supply)

1. Before installation please ensure there is sufficient air space around LCD unit for ventilation.
2. Remove from box and unpackage lens and screen panel.
3. Carefully remove protective film from both sides of lens
4. Mount the lens by screwing the lens to the panel using four screws (one per corner). These should be counter sunk, 0.39" M3 screws.
5. Attach the screen with mounted lens to the fixing studs behind COP panel using a flat and spring washer on each stud before engaging nut.
6. Mount speaker if desired.
7. Power supply must be mounted within 4' but no closer than 3'.
8. Plug power socket into display.
9. Connect 240v main power to the power supply\*.

\* Please adhere to instructions on power supply.

## Mounting Instruction (Processor)

1. Mount Processor using mounting holes on the fixed bracket and add a flat and a spring washer before engaging nut.
2. Processor's power supply must also be mounted within 4' but no closer than 3'.
3. Plug power supply into processor.
4. Plug cable (HDMI/VGA) into processor and connect to display.
5. Power up the system.
6. The screen should become active.

