



Part #: AC-4CM10-640-F-20-000

Features

- The Cellular Gateway uses 4G LTE technology and is fully code compliant
- If the connected elevator phone is not equipped with external power, you must order Janus part # POWPK-12VC
- The cellular software checks the network connection throughout the day and if the network connection is compromised, the software will alert the Janus phone which will provide a trouble signal to the Communication Failure Annunciator until the network has been restored
- Standard FXS port to allow a 2-wire connection from elevator phone, EMS5, or MRI
- Includes RS232 serial connector and CANBUS connector
- Use as a pass through for controller logic on a wireless platform
- Surface mounted
- Includes antenna
- FCC registered
- UL 62368-1 listed
- **Internal Battery:** 12v, 800mAh (meets ASME requirements for 4 hours talk time)
- **Voltage Rating:**
Idle: 110-120v, 50/60Hz, current draw 40mA
Active: Current draw 80mA
- **Dimensions:** 4.3" H x 8.3" W x 2.6" D
- **Power Requirements:** 120vac, 10VA

AT&T SIM Card & 4G LTE Plan Requirements

- Standard size AT&T SIM card (25mm x 15mm)
- Business data plan with voice capabilities OR
- Janus 2-year plan (part # ATTPLAN-2)
- Disable voicemail and call waiting