

The PBX elevator phone is fully ADA compliant and made to fit into your elevator's phone cabinet. This phone has the reliability and features that you have come to expect from EMS products.



Part #: PBX

Features:

- Phone line powered
- ADA compliant
- Phone line monitoring available
- On board keypad
- Optional on board relay
- Surface mount in a phone cabinet or wall
- Built in four number dialer
- Extended voice chip capability
- Easy installation and programming
- Fully programmable voice chip
- Available in one or two LED version
- FCC Registered
- CSA Listed
- Two year warranty
- Positive acknowledgement of alarm received
- Tone activated (not fooled by voicemail or other recordings)
- Voice prompts reduce operator error

Specifications:

- **Dimensions:** 8.93" H x 4.90" W x 2.09" D
- **Weight:** 1/2 lb.
- **Frequency Response:** 550Hz - 3400Hz, +/- 3db
- **Dialing:** DTMF (Dual Tone Multi Frequency)
- **Ring Sensitivity:** 40-120vac RMS
- **REN:** 0.2B
- **Loop Current Range:** 10mA to 60mA (20mA typical)
- **Optional AC adaptor:** 12vdc@500mA
- **Operating Current Range:** 25mA to 55mA
- **Power:** Telephone line powered (48vdc to 50vdc typical)
- **Relative Humidity:** Up to 95% (non-condensing)
- **Operating Temp:** -40 to 185 degrees F
- **Industry Canada No.:** C22.2 No.60950-1-01, 2nd Ed
- **FCC Reg. No.:** US: NLFTE05B25668
- **Mounting Type:** Surface Mount