



1032 Canopy



2026 Burlap



7035 Chestnut



9022 Sable



5054 Greystone

NORTHINGTON BRUSHED



Style Number	SW670
Construction	Epic Plus
Thickness	1/2" (11.93mm)
Width	4.94"
Species	Hickory
Texture	Wire Brushed
Gloss Level	7%
Janka Hardness Rating	1787
Edge Description	Microbeveled
End Description	Microbeveled
SF per carton	15.80
SF per pallet	948.00
Installations	Nail, Staple, Glue, Float
All measurements are nominal	Cartons may include random lengths

Features

- Rich hickory character showcased in traditional & contemporary color palette
- Also available in smooth version SW669 Northington Smooth


Sundry Recommendations

Style #	Style Name	Coverage	Moisture Test	
ADHESIVES				
HS105	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH	
111SA	3-in-1 Ultra — MS	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH	
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required	
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH	
		60 SF / gal	Up to 5 lbs. or 85% RH	

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH12
Flush Reducer



SORH2
*Overlap Reducer



SSH12
Flush Stairnose



SOSH2
*Overlap Stairnose



SCH12
Threshold | Carpet Reducer



TMH78
T-Molding



QTR96
Quarter Round

Benefits

