



Key Digital Presentation Solutions are a family of products integrating a Soft-Codec Enabling System with HDBT/HDMI/Audio/Control hardware designed for professional audio video installations in conference rooms, board rooms, classrooms, lecture halls, auditoriums, and more.



KD-CAMUSB

PTZ USB Camera, IR/RS-232/Visca Controllable

KEY FEATURES

- ▶ **USB 2.0 Pan-Tilt-Zoom Camera:** Professional USB camera ideal for Video Conferencing and Capture applications in Huddle Spaces, Conference Rooms, Board Rooms, Lecture Halls, and more.
- ▶ **Compatible Operating Systems:** Generic USB Video Class Driver for effortless use on Windows 7, Windows 10, Mac OS X, and Linux machines
- ▶ **Video Conference Software Support:** Delivers professional PTZ features for popular video conference software such as Skype®, GoToMeeting®, Microsoft Teams®, Zoom™, RingCentral®, Google® Hangouts, and more
- ▶ **Soft Conference Enabling System:** Use with Key Digital Presentation Solutions family including KD-UPS52U, KD-PS22UTx, KD-X4x1WUTx, KD-X3x1WUTx, and KD-X100MRx to add USB plug-in wall plates, USB/KVM routing and extension, Digital Video switching, integration with professional audio visual systems (use external microphones as KD-CAMUSB does not feature built-in mic), TCP/IP and KD-App ready control.
- ▶ **Multiple Mounting Options:** Wall, and ceiling mounting hardware included. May also be table surface mounted.
- ▶ **Recall & Store Position Presets:** Up to 255 presets may be created, with up to 12 presets accessed via IR remote control on Home, Privacy, and numeric buttons.
- ▶ **Auto Focus:** Fast and accurate auto focus via leading auto focus algorithm
- ▶ **Video Resolutions:** From 320x240p @ 30fps up to 1920x1080p @ 30fps. Adjustable via Windows camera viewer and conferencing software camera settings panels
- ▶ **Pan-Tilt-Zoom:** Pan = $\pm 170^\circ$. Tilt = -30° to $+90^\circ$. Zoom = 10x
- ▶ **User-Friendly IR Remote:** Provides intuitive and ergonomic control
- ▶ **RS-232:** Bi-Directional control to/from KD-CAMUSB or via Key Digital Presentation Solutions Extender & Switcher units
- ▶ **VISCA Controllable:** Responds to VISCA protocol for control by PTZ camera control consoles. Supports addressing for multi-camera systems.



- ▶ **Control System Support:** Fully controllable by all RS-232 supported control systems via open API: Compass Control® Pro, AMX®, Crestron®, KNX®, RTI®, Savant, URC®, Leviton® etc. TCP/IP controllable when integrated with supported Key Digital Presentation Solutions Extenders and Switchers.
- ▶ **KD-App Ready:** When integrated with supported Key Digital Presentation Solutions Extenders and Switchers including KD-UPS52U, KD-X4x1WUTx, and KD-X100MRx. Pre-built GUI populates offering PTZ controls as source selection and display/projector controls via CEC Manager™.

SPECIFICATIONS

- » Regulation: CE, RoHS, WEEE, EAC
- » Enclosure: Silver Plastic

SYSTEM DESIGN EXAMPLE

