




## CA-HM

Active High Speed HDMI™ Cable  
with Ethernet



The Kramer CA-HM active HDMI™ copper cable provides a perfect cable solution for delivering HDMI signal over long distances. CA-HM runs 18Gbps up to 20m (66ft), 10.2Gbps up to 25m (82ft), and 6.75Gbps up to 30m (98ft). The innovative technology utilized in the cable's connector features superior equalizing and signal compensation to meet the most demanding challenges in Pro AV installations.

This unique solution simplifies long distance installations by using a true plug & play cable that draws power from the HDMI™ source, without requiring an external power source. CA-HM features the Kramer exclusive K-Lock™ HDMI™ connector, securing your installation from unintentional cable disconnections and eliminating cable-related service calls. Additionally, a LED on the connector indicates successful signal transmission.

\* CA-HM is a directional cable.




### Features

- Video Resolution: Up to 4K@60Hz (4:4:4)
- High Data Transfer Rate: Up to 18Gbps
- HDMI Support: HDCP 2.2, HDR, EDID, ARC and CEC
- Deep Color and x.v.Color™, 5.1/7.1 lossless Dolby® TrueHD and DTS-HD Master Audio®
- High-quality Connectors: 24K gold-plated, corrosion-resistant and best possible connectivity
- Pull-resistant: K-Lock™ connectors with 15lbs of restraining force
- Triple shielded for maximum EMI protection
- UL listed, CL3/FT4 rated for in-wall installations
- Varied Selection of Lengths: Available in versions of 15 to 98ft (4.6 to 30m)





Non-slip connection with  
15lbs of restraining force



## CABLE SPECIFICATIONS

### AUDIO & VIDEO SPECIFICATIONS

<b>Video Resolution</b>	15-66ft (4.6-20m): Up to 4K60 4:4:4; 82ft (25m): Up to 4K60 4:2:0; 98ft (30m): Up to 1080p@60Hz 12-Bit
<b>Data Rate (max)</b>	15-66ft (4.6-20m): Up to 18Gbps; 82ft (25m): Up to 10.2Gbps; 98ft (30m): Up to 6.75Gbps
<b>Supported Audio Formats</b>	Dolby® Digital Plus, Dolby® TrueHD, DTS-HD Master Audio®, DVD Audio, SA-CD
<b>HDMI Compliance</b>	HDCP 2.2, HDR, EDID and CEC

### PHYSICAL SPECIFICATIONS

<b>Connector-1 (source end)</b>	Male HDMI Type A, 24K gold-plated K-Lock connector
<b>Connector-2 (display end)</b>	Male HDMI Type A, 24K gold-plated K-Lock connector (optional external power input via Micro USB connector)
<b>Conductors</b>	15ft (4.6m): 32AWG; 25-35ft (7.6-10.7m): 28AWG, 50ft (15.2m): 26AWG; 66-98ft (20-30m): 24 AWG
<b>Shielding</b>	TMDS pairs: aluminum/mylar Overall: aluminum/mylar + aluminum braid
<b>Outer Sheath Material</b>	PVC
<b>Outer Sheath Color</b>	Black
<b>Outer Sheath Diameter</b>	15ft (4.6m): 5.5±0.15mm; 25-35ft (7.6-10.7m): 7.10±0.15mm 50ft (15.2m): 8.5±0.20mm; 66-98ft (20-30m): 9.5±0.25mm
<b>Cable Bending Radius</b>	15ft (4.6m): 27.5mm; 25-35ft (7.6-10.7m): 35.5mm 50ft (15.2m): 42.5mm; 66-98ft (20-30m): 47.5mm
<b>Connector Max. Pulling Strength</b>	15lbs/6.8kg

### ELECTRICAL SPECIFICATIONS





<b>Temperature Rating</b>	80°C
<b>Voltage Rating</b>	30V
<b>Conductor Resistance</b>	32AWG: 588 Ω/km; 28AWG: 237.25588 Ω/km 26AWG: 148.94 Ω/km; 24AWG: 381 Ω/km
<b>Power Consumption</b>	90mA (18Gbps) / 1mA (standby mode)

### REGULATORY





<b>Rating</b>	UL listed, CL3/FT4
<b>RoHS</b>	2011 / 65 / EU

## OUTLINE DIMENSIONS

### 15-35ft



### 50-98ft





## ORDERING INFORMATION

MODEL	DESCRIPTION	LENGTH	RESOLUTION
<b>CA-HM-15</b>	Active High Speed HDMI™ Cable with Ethernet	15ft / 4.6m	4K@60Hz (4:4:4)
<b>CA-HM-25</b>	Active High Speed HDMI™ Cable with Ethernet	25ft / 7.6m	4K@60Hz (4:4:4)
<b>CA-HM-35</b>	Active High Speed HDMI™ Cable with Ethernet	35ft / 10.7m	4K@60Hz (4:4:4)
<b>CA-HM-50</b>	Active High Speed HDMI™ Cable with Ethernet	50ft / 15.2m	4K@60Hz (4:4:4)
<b>CA-HM-66</b>	Active High Speed HDMI™ Cable with Ethernet	66ft / 20m	4K@60Hz (4:4:4)
<b>CA-HM-82</b>	Active High Speed HDMI™ Cable with Ethernet	82ft / 25m	4K@60Hz (4:2:0)
<b>CA-HM-98</b>	Active High Speed HDMI™ Cable with Ethernet	98ft / 30m	1080p@60Hz 12-Bit

