

Specifications



	PowrLiner™ 550	PowrLiner™ 850	PowrLiner™ 1800M
Part #: 1-Gun 2-Gun 1-Gun (Self-Propelled) 2-Gun (Self-Propelled)	0290004 — — —	0290005 — — —	759-191 — — —
Max. Tip Size: (Gas) 1-Gun 2-Gun (Electric) 1-Gun 2-Gun	0.019" — — —	0.021" (.017 Airless painting) — — —	0.023" — — —
Max. Output: (Gas) (Electric)	.33 GPM (1.3 lpm) —	.33 GPM (1.3 lpm) —	.50 GPM (1.9 lpm) —
Max. Spraying Speed*	106 linear ft. (32.3 m) per minute @ 1.2 mph (1.9 kph)	106 linear ft. (32.3 m) per minute @ 1.2 mph (1.9 kph)	240 linear ft. (73.2 m) per minute @ 2.7 mph (4.3 kph)
Line Width Range	2" - 12" (5 cm - 30.5 cm)	2" - 12" (5 cm - 30.5 cm)	2" - 12" (5 cm - 30.5 cm)
Max. Operating Pressure	3000 PSI (17.2 MPa)	3000 PSI (17.2 MPa)	3300 PSI (22.8 MPa)
Max. Hose Length	50' (15.2 m)	50' (15.2 m)	300' (91.4 m)
Power Source	37.7cc 4 stroke Engine	37.7cc 4 stroke Engine	126cc Subaru® OHC Engine w/Low-Oil Alert
Electric Motor	—	—	—
Pump Drive	Clutch Driven	Clutch Driven	Clutch Driven
Cycle Rate	—	—	—
Electrical System	—	—	—
Paint Outlet: Filter Element Filter Area	60 mesh 3 in ² (19 cm ²)	60 mesh 3 in ² (19 cm ²)	60 mesh 14 in ² (90 cm ²)
Airless Gun	550-540, LX-40	550-540, LX-40	550-540, LX-40
Airless Hose	0315265, 1/4" x 50' (7.5 m)	0315265, 1/4" x 50' (7.5 m)	316-505, 1/4" x 50' (15.2m)
Airless Striping Tips supplied per gun	1 ea., 665-1908, SC-6™ Striping Tip, 4" Line by .019" orifice	1 ea., 665-1908, SC-6™ Striping Tip, 4" Line by .019" orifice	1 ea., 665-1908, SC-6™ Striping Tip, 4" Line by .019" orifice
Operator's Manual	313-2300	313-2300	313-2797
Repair Kit: Pump Gun	759-365 N/A	759-365 N/A	755-165 N/A
Optional Electric Motor Kit	—	—	—
Weight: Unit	67 lbs (30 kg)	67 Lbs (31 kg)	145 lbs (66 kg)
Weight: Unit Crated	75 lbs (34 kg)	75 lbs (34 kg)	170 lbs (77 kg)
Dimensions: Unit	38" H x 29" W x 42" L (97 cm H x 74 cm W x 107 cm L)	38" H x 29" W x 42" L (97 cm H x 74 cm W x 107 cm L)	41" H x 30" W x 54" L (104 cm H x 79 cm W x 152 cm L)
Dimensions: Unit Crated	24" H x 26" W x 46" L (61 cm H x 66 cm W x 116 cm L)	24" H x 26" W x 46" L (61 cm H x 66 cm W x 116 cm L)	49" H x 33" W x 64" L (125 cm H x 84 cm W x 163 cm L)
Dimensions: PowrHandler	—	—	—
Dimensions: PowrHandler Crated	—	—	—

*Based on 4" (10 cm) line @ 15 mil wet film thickness and 320 linear feet per gallon coverage.

All information contained in this brochure is based on the latest information available at the time of printing. Titan reserves the right to make changes at any time without notice.