

**Part #: 2100-LTEVER4****Features**

- The Cellular Gateway uses 4G LTE technology and is fully code compliant
- Compatible with all RATH® SmartPhone VI elevator phones
- The cellular software checks the network connection throughout the day and if the network connection is compromised, the software will alert the SmartPhone which will provide a trouble signal to the Communication Failure Annunciator until the network has been restored
- Standard FXS port to allow a 2-wire connection from elevator phone, machine room phone, or lobby master
- Includes RS232 serial connector and CANBUS connector
- Use as a pass through for controller logic on a wireless platform
- Surface mounted
- Includes antenna
- FCC registered
- UL 62368-1 listed
- **Internal Battery:** 12v, 800mAh (meets ASME requirements for 4 hours talk time)
- **Voltage Rating:**
Idle: 110-120v, 50/60Hz, current draw 40mA
Active: Current draw 80mA
- **Dimensions:** 4.3" H x 8.3" W x 2.6" D
- **Power Requirements:** 120vac, 10VA

Verizon 4G LTE Plan & SIM Card Requirements

The customer must have access to a Verizon Business Manager to manually modify the account.

- Flex Data Plan required
 - Add access HD voice
 - Remove call waiting
 - Remove voicemail
- Standard size Verizon SIM card (25mm x 15mm) required