

2300-630MRO Machine Room Rescue Features:

- Ideal for the machine room
- Telephone line powered
- Requires two analog telephone lines (POTS, PBX, or central office phone lines) for operation. One is for the device and one is for the elevator phone (if only a single line is available, see the SmartRescue).
- Requires separate twisted, shielded line run to the main phone line supplying the SmartPhones
- Lift handset and unit automatically calls all cars and at that point you can toggle between each car
- Unit automatically disconnects outside world and only allows communication to the elevators
- Volume control handset meets ADA requirements
- 3 year warranty



ASME A17.1 Code:

- Where the elevator travel is 18m (60ft) or more, two-way voice communication means within the building shall be provided and comply with the following:
 - a) The means shall enable emergency personnel within the building to establish two-way voice communication to each car individually. Two-way voice communications shall be established without any intentional delay and shall not require intervention by a person within the car.
 - b) Two-way voice communications, once established, shall be disconnected only when emergency personnel outside the car terminate the call.

Canada B44 2.27.1.1.4 & 2.3.2 Code:

- Where travel exceeds 18m, verify conformance and operation of requirements a-d:
 - a) An on-site building communications station must be provided to initiate two-way voice communication into each elevator individually without delay and must not require intervention from persons in the car.
 - b) The initiating of communication via the on-site building station location shall override any communications underway between the car and any communications to outside the building.
 - c) A visual signal shall acknowledge the establishment of this communications link and extinguish when the link is terminated. Only communication stations other than the in-car station can terminate an established communications link.
 - d) Instructions for operation of the two-way voice communication system shall be provided at the on-site building communication station.
- An on-site communication station shall be provided and its location shall be accessible to authorized and emergency personnel as required by 2.27.1.1.1. A locked building manager's office or machine room is not an accessible location.