

**Command Center Cabinet  
(Surface Mount)**



**System Includes Phone  
& Distribution Module**

- 10 Zone 2500-10RCV
- 16 Zone 2500-16RCV
- 32 Zone 2500-32RCV
- 48 Zone 2500-48RCV
- 64 Zone 2500-64XRCV
- 80 Zone 2500-80XRCV
- 96 Zone 2500-96XRCV
- 112 Zone 2500-112XRCV
- 128 Zone 2500-128XRCV

**Dimensions:**

- 2500-10RCV, 16RCV: 15.14" H x 12" W x 6.19" D
- 2500-32, 48, 64, 80, 96, 112, 128(X)RCV: 21.03" H x 20.3" W x 5.19" D

**Command Center Cabinet  
(Flush Mount)**



**System Includes Phone  
& Distribution Module**

- 10 Zone 2500-10RCFV
- 16 Zone 2500-16RCFV
- 32 Zone 2500-32RCFV
- 48 Zone 2500-48RCFV
- 64 Zone 2500-64XRCFV
- 80 Zone 2500-80XRCFV
- 96 Zone 2500-96XRCFV
- 112 Zone 2500-112XRCFV
- 128 Zone 2500-128XRCFV

**Dimensions:**

- 2500-10RCFV, 16RCFV:
  - Front Frame: 16.06" H x 14" W x 3.07" D
  - Back Box: 15.64" H x 12" W x 3" D
- 2500-32, 48, 64, 80, 96, 112, 128(X)RCFV:
  - Front Frame: 21.13" H x 25" W x 3.06" D
  - Back Box: 20.66" H x 23" W x 3" D

**Command Center  
(Desk Mount)**



**System Includes Phone  
& Distribution Module**

- 10 Zone 2500-10NCV
- 16 Zone 2500-16NCV
- 32 Zone 2500-32NCV
- 48 Zone 2500-48NCV
- 64 Zone 2500-64XNCV
- 80 Zone 2500-80XNCV
- 96 Zone 2500-96XNCV
- 112 Zone 2500-112XNCV
- 128 Zone 2500-128XNCV

**Contact Us for  
Larger Projects**

**IP Command Center:**

- Surface cabinet, flush cabinet, or desk mount
- Powder coated steel enclosure with twist lock closure
- Includes handset and speaker phone for communication to elevators
- Command Center and Sub-Master Stations are powered from the Distribution Module (IP based units require PoE)
- Works with In Car Analog Phones with Remote IP Interface or In Car IP Phones
- Can be configured with the main Command Center, Multiple Sub-Master Stations (available in desk, surface, or flush mount) and Machine Room phones (2300-630RC)
- Command Center and Sub-Master Stations to Distribution Module: Single pair or via IP (contact RATH® for a quote on the IP version)
- In Car Analog Phone and 2300-630RC require a 2100-VOIP2CS Interface. The In Car IP Phones are a direct Ethernet connection.
- Connect 2100-VOIP2CS and In Car IP Phone to Distribution Module via an Ethernet connection. Maximum 300' run to Network Switch.
- SmartPhones to Distribution Module: Ethernet
- System requires an analog telephone line, an IP phone line when used with the RATH® 2100-VOIP2CS Interface Device, or can be set up as an IP Intercom System
- Audible alert sounds when phones place a call until Command Center joins conversation
- LEDs indicate which phones have initiated a call
- Rescue personnel can communicate with individual phones and outside party
- Calls wait in queue until previous call is disconnected and receive a message stating that an emergency call is in progress. When the prior call clears, the next phone in queue is connected.
- ADA, ASME A17, and B44 code compliant
- 3 year warranty

**Distribution Modules**



**10-48 Zone System**



**64-128 Zone System**

- Included with Command Center
- Surface mount
- Install on a wall or table top
- Requires 120vac power with battery backup or RATH® Power Supply with battery backup
- Single dedicated phone line or as an Intercom System

**Dimensions:**

- 10-48 Zone System: 2.04" H x 17.28" W x 11.8" D
- 64-128 Zone System: 6.83" H x 17.18" W x 8.9" D