



## 2100 Series Features

- Wireless options only work with the current 2100 Series phones
- Phone is designed for 120vac or 24vac/vdc power
- Programmable with up to 5 emergency telephone numbers
- Location message (18 seconds) with Human Voice Recognition
- On-site programming
- Pictorial keypad
- Built-in battery backup recharges from 120vac or 24vac/vdc power. Allows for a minimum of 4 hours of talk time upon loss of power
- Temperature range -40F to +150F
- Automatic dialer (31 digit programmable memory)
- Programming error indicator
- Automatic answer feature
- ADA compliant speaker phones (meets all requirements of ADA, ASME A17 and B44 Codes for elevator emergency phones)
- 3 year warranty

## Cellular Features

- The cellular interface is available in GSM cellular technology
- Interface model number: 2100-GSM4
- GSM carriers are AT&T or a pre-paid SIM card (both require a 4G SIM card for operation)
- End user contracts directly with a cellular provider
- The 2100-GSM4 requires 120vac power
- Requires two wire connection from elevator phone to cellular device
- Surface mounted either remotely (standard) or in elevator if there is a strong signal (requires additional equipment)
- Requires a 15mm x 25mm 4G SIM card
- Requires a “voice” only plan (no data or voicemail)
- Includes cellular antenna

