



Flush Mount Model Numbers:

- 12 Zone 2500-12FSV
- 16 Zone 2500-16FSV
- 28 Zone 2500-28FSV
- 36 Zone 2500-36FSV
- 56 Zone 2500-56XFSV
- 76 Zone 2500-76XFSV
- 96 Zone 2500-96XFSV
- 116 Zone 2500-116XBSV

Front Frame Dimensions: 21.13" H x 25" W x 3.06" D

Back Box Dimensions: 20.66" H x 22.99" W x 3" D



Surface Mount Model Numbers:

- 12 Zone 2500-12BSV
- 16 Zone 2500-16BSV
- 28 Zone 2500-28BSV
- 36 Zone 2500-36BSV
- 56 Zone 2500-56XBSV
- 76 Zone 2500-76XBSV
- 96 Zone 2500-96XBSV
- 116 Zone 2500-116XBSV

Dimensions: 21.03" H x 20.3" W x 5.19" D

Sub-Master Station:

- Surface or flush cabinet
- Powder coated steel enclosure with twist lock closure
- Includes handset for communication to elevators
- Sub-Master Stations to Distribution Module: Single pair
- SmartPhones to Distribution Module (single pair)
- Can be configured with the main Base Station, multiple Sub-Master Stations (available surface or flush mount)
- Works with our model 2100 series SmartPhones
- Audible alert sounds when phones place a call until Base Station or Sub-Master Station joins conversation
- LEDs indicate which phones have initiated a call
- Rescue personnel can communicate with individual phones and outside party
- Calls wait in queue until previous call is disconnected
- ADA, ASME A17, and B44 code compliant
- 3 year warranty

SmartView Display & Controller Features:

- **Power Connections:** 120v
- Ethernet connection
- HDMI connection for display