

5821



Wireless Temperature Sensor & Flood Detector

Honeywell's 5821 is a versatile wireless device that can be configured to operate as either a standalone temperature sensor and/or a remote temperature sensor or flood detector. It is ideally suited for a wide range of applications including bathrooms, laundry rooms and basements.

FEATURES

- Five selectable temperature ranges to choose from (Hot, Warm, Cold, Refrigerate and Freeze)
- Remote Temperature Probe available (T280R) ideal for refrigerator and freezer monitoring
- Flood detection with 470PB External Probe for a wide range of applications; including bathrooms, laundry rooms and basements.
- Up to 10 year battery life, which reduces user maintenance.
- Completely wireless, which greatly reduces installation time and maximizes placement options.
- Capable of monitoring cold (45°F) temperature and flood detection simultaneously

SPECIFICATIONS

Sensor Parameters

- Cold Temperature Detector 45°F
 - When temperature drops below 45°F for >10 minutes
- Warm Temperature Detector 75°F
 - When temperature rises above 75°F for >10 minutes
- Hot Temperature Detector 95°F
 - When temperature rises above 95°F for >10 minutes
- Refrigerator Failure Detector 42°F
 - When temperature rises above 42°F for >30 minutes
- Freezer Failure Detector 10°F
 - When temperature rises above 10°F for >30 minutes
- Flood Sensor
 - When 1/4" inch of water is covering the 470PB probe
- "Swinger Suppression" (Hysteresis) of 3°F
 - Temperature difference between fault and restore points

Power

- One 3V battery (included)
- Replace only with ADEMCO #466, Panasonic CR123A, Sanyo CR123A, Duracell DL123A, Tekcell CR123A or Varta CR123A (Lithium Manganese Dioxide)

Case Tamper Protection

Operating Temperature

- 14°F to 104°F (-10°C to +40°C)

Operating Frequency

- 345 MHz ± 85 KHz

Range of Response time

- +50%, -20%
 - 10 minute setting (8-15 min)
 - 30 minute setting (24-45 min)

Dimensions

- 1.6"W x 3.1"H x 1.0"D (max protrusion)
- (40.64mm x 78.74mm x 25.4mm)

Compatibility

- Compatible with all 5800 series wireless receivers.

Agency Listings

- FCC Part 15
- DOC RSS-210

ORDERING

5821	Wireless Temperature Sensor & Flood Detector
T280R	External Probe for Freezer and Refrigeration Monitoring
470PB	External Probe for Flood Sensing



T280R



470PB

Honeywell Security & Custom Electronics

Honeywell International Inc.

PO Box 9035

Syosset, NY 11791

www.honeywell.com

L/5821/D
June 2005

©2005 Honeywell International Inc.

Honeywell