



# Material Safety Data Sheet

**APPLICANT** : SWIT Electronics Co., Ltd.  
**ADDRESS** : 10 Heng Tong Road, Xin'gang Nanjing Economic and Technological Development Zone Nanjing 210038, P.R.China  
**BRAND NAME** : SWIT  
**SAMPLE NAME** : Li-ion Battery Pack  
**MODEL NAME** : S-8U95  
**ISSUE DATE** : 2018/08/14

**SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.**

Checked by : He Xueqian  
He Xueqian  
Approved by : Li Dong  
Li Dong

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



# 1. Chemical Product and Company Identification

Product Name	Li-ion Battery Pack
Model Name	S-8U95
Rating	14.4 V / 6.8 Ah, 98 Wh
Manufacturer	SWIT Electronics Co., Ltd.
Manufacturer Address	10 Heng Tong Road, Xin'gang Nanjing Economic and Technological Development Zone Nanjing 210038, P.R.China
Emergency Telephone Number	+86-25-85582170

## 2. Hazards Identification

### Route(s) of Entry

There is no hazard when the measures for handling and storage are followed.

### Signs and Symptoms of exposure

In case of cell damage, possible release of dangerous substances and a flammable gas mixture

**OSHA Hazard communication: this material is not considered hazardous by the OSHA**

**Hazard communication Standard 29CFR 1910.120.**

Carcinogenicity (NTP): Not listed

Carcinogenicity (IARC): Not listed

Carcinogenicity (OSHA): Not listed

### Special hazards for human health and environment

There is no hazard when the measures for handling and storage are followed.

In case of cell damage, possible release of dangerous substances and a flammable gas mixture

## 3. Composition Information

The battery pack uses eight SANYO NCR18650GA Lithium-ion rechargeable cells and control circuit on the PCB. The cells are connected in 2 parallel strings of 4 cells in series.

Hazardous Ingredients	CAS Number	Approximate% of total weight
Lithium Cobalt Oxide (LiCoO <sub>2</sub> )	12190-79-3	20~60
Aluminum Foil (Al)	7429-90-5	1~30
Poly Vnylidene Fluoride PVDF(-[-CH <sub>2</sub> -CF <sub>2</sub> ]-n)	24937-79-9	1.0
Graphite (C)	7782-42-5	10~30
Copper Foil (Cu)	7440-50-8	1~15
Organic electrolyte principally involves ester carbonate	—	5~25



## 4. First Aid Measures

### General information

The following first aid measures are required only in case exposure to interior battery components after damage of the external battery casing.

Undamaged, closed cells do not represent a danger to the health.

### Skin contact

If skin contact with contents of open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

### Eye contact

If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.

### Inhalation

If contents of an opened battery are inhaled, remove source of contamination or move victim to fresh air. Obtain medical advice

### Ingestion

If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. Call a physician.

## 5. Fire Fighting Measures

### Suitable extinguishing media

Cold water and dry powder in large amount are applicable.

Use metal fire extinction powder or dry sand if only few cells are involved

### Specific Hazards arising from the chemical

May form hydrofluoric acid if electrolyte comes into contact with water.

In case of fire, the formation of the following flue gases cannot be excluded: Hydrogen fluoride (HF), Carbon monoxide and carbon dioxide.

### Protective Equipment and precautions for firefighters

As for any fire, evacuate the area and fight the fire from a safe distance.

Wear a pressure-demand, self-contained breathing apparatus and full protective gear.

Fight fire from a protected location or a safe distance.

### Flammable Properties

In the event that this battery has been ruptured, the electrolyte solution contain within the battery



would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.

## 6. Accidental Release Measures

### Personal Precautions

Restrict access to area until completion of clean-up.

Do not touch the spilled material.

Wear adequate personal protective equipment as indicated in Section 8

### Environmental Precautions

Prevent material from contaminating soil and from entering sewers or waterways.

Methods for cleaning up/taking up

Take up mechanically and send for disposal.

### Methods and materials for containment

Stop the leak if safe to do so.

Contain the spilled liquid with dry sand or earth.

Clean up spills immediately.

## 7. Handling and Storage

### Handling

#### **Advice on safe handling**

Avoid short circuiting the cell. Avoid mechanical damage of the cell.

Do not open or disassemble.

Don't handling Lithium Ion Battery with metalwork.

Advice on protection against fire and explosion,

Ensure good ventilation/exhaustion at the workplace.

### Storage

Requirement for storage rooms and vessels

Storage the cell at temperature  $-20^{\circ}\text{C} \sim +45^{\circ}\text{C}$ , low humidity and no corrosive gas atmosphere.

In case of long period storage (more than 3 months), storage the cell at temperature range of  $-10^{\circ}\text{C} \sim +20^{\circ}\text{C}$ , low humidity and no corrosive gas atmosphere.

The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.

Do not storage Lithium Ion Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects

Keep out of reach of children.

Do not expose Lithium Ion Battery to heat of fire.

Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.



## 8. Exposure Controls/Personal Protection

### Safe guard procedures

#### Engineering Controls

Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor.

Keep away from heat and open flame. Store in a cool, dry place.

#### Personal Protective Equipment

**Respiratory Protection:** Not necessary under normal conditions.

**Skin and body Protection:** Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery.

**Hand protection:** Wear neoprene or natural rubber material gloves if handling an open or leaking battery.

**Eye Protection:** Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.

#### Other Protective Equipment

Have a safety shower and eye wash fountain readily available in the immediate work area.

#### Hygiene Measures

Do not eat, drink, or smoke in work area.

## 9. Physical and Chemical Properties

### Appearance

Appearance & Odor Rectangle shape, Odorless

### Important health, safety and environmental information

Change in condition	Not available
PH, with indication of the concentration	Not available
Melting point/freezing point	Not available
Boiling Point, initial boiling point and boiling range	Not available
Flash Point	Not available
Upper/Lower flammability or explosive limits	Not available
Density/relative density	Not available
Solubility in Water	Insoluble
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Flammability (soil, gas)	Not available
Viscosity	Not available



## 10. Stability and Reactivity

### Stability

The product is stable under normal conditions.

### Conditions to avoid

Do not subject Lithium Ion Battery to mechanical shock.

Vibration encountered during transportation does not cause leakage, fire or explosion.

Do not disassemble, crush, short or install with incorrect polarity.

Avoid mechanical or electrical abuse.

### Materials to avoid

No materials to be especially mentioned

### Hazardous decomposition products

In case of open cells, there is the possibility of hydrofluoric acid and carbon monoxide release.

### Possibility of Hazardous Reactions

Will not occur

### Additional information

No decomposition if stored and applied as directed.

## 11. Toxicological Information

### Irritation

Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.

### Sensitization

Not Available

### Neurological Effects

Not Available

### Reproductive Toxicity

Not Available

### Mutagenicity (Genetic Effects)

Not Available

### Toxicologically Synergistic Materials

Not Available

## 12. Ecological Information

### Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.



## 13. Disposal Considerations

Disposal of the battery should be performed by permitted, professional disposal firms knowledgeable in Federal, State or Local requirements of hazardous waste treatment and hazardous waste transportation.

## 14. Transport Information

**With regard to transport, the following regulations are cited and considered**

- The International Maritime Dangerous Goods (IMDG) Code by International Maritime Organization (IMO), Dangerous Goods Regulations (DGR) by International Air Transport Association (IATA) and Technical Instructions for the Safe Transport of Dangerous Goods by Air (TI) by International Civil Aviation Organization (ICAO). These regulations are based on the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.
- The International Civil Aviation Organization (ICAO) Technical Instructions, Packing Instruction 965-967, Section IB or II (2017-2018 Edition)
- The International Air Transport Association (IATA) Dangerous Goods Regulations, Packing Instruction 965-967, Section IB or II (59<sup>th</sup> Edition, 2018). For cells, the Watt-hour rating should not be more than 20Wh; For batteries, the Watt-hour rating should not be more than 100Wh. Watt-hour rating must be marked on the outside of the battery case.
- The International Maritime Dangerous Goods (IMDG) Code (2016Edition), [Special provision 188, 230]
- The US Hazardous Materials Regulations 49 CFR (Code of Federal Regulations) Sections 173-185 Lithium batteries and cells
- The UN classification number: Class 9 3480(lithium ion batteries) / 3481(lithium ion batteries contained in equipment or lithium ion batteries packed with equipment)
- The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries, Rev.6, Amend.1

## 15. Regulatory Information

### Regulatory information EU

#### Labeling

#### Hazardous components which must be listed on the label

As an article the product does not need to be labeled in accordance with EC directives or respective national laws.

According to Directive 2012/19/EU, the batteries have to be marked with the crossed wheel bin symbol.

According to Dangerous Goods Regulations, the battery packs have to be marked with the Watt-hour rating.

#### U.S. Regulations



### **National Inventory TSCA**

All of the components are listed on the TSCA inventory.

### **SARA**

To the best of our knowledge this product contains no toxic chemicals subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

## **16. Other Information**

The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.

This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

### **DISCLAIMER**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. We make no warranty of merchant ability or any other warranty express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes. In no way shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental consequential or exemplary damages, howsoever arising from using the above information.

**\*\*\*\*\* End of Material Safety Data Sheet \*\*\*\*\***