

BAT WIFI

Wi-Fi & Internet Alarm Communicator

SKU: IPD-BAT-WIFI

With ipDatatel's unique alarm communicators, you can provide your customers with the best solutions while protecting your business against future cellular sunsets. Features the very latest technology, remote panel programming and universal panel support - including Honeywell, DSC and GE/Caddx. The BAT WIFI is a cost-effective Wi-Fi & Internet alarm communicator featuring fast IP alarm communications and industry-leading remote service capabilities.



UNIVERSAL PANEL COMPATIBILITY

Works with most alarm systems with Contact ID



SIMPLE INSTALLATION

Wi-Fi via WPS and Ethernet



REMOTE PANEL PROGRAMMING

Saves time and virtually eliminates costly truck rolls



EVENT NOTIFICATIONS

Get alerts via text/push, email and digital voice call



CONTROL ON THE GO

Arm/disarm the system using a mobile device or PC



WIFI



ETHERNET

PANEL COMPATIBILITY

Works with most keyswitch connected panels using CID, including HAI OmniPro, Napco,

Honeywell

Honeywell Vista series panels are fully supported

Vista 10P	Vista 20P/PS/PCN
VISTA 10PSIA	Vista 20PI
Vista 128BP	Vista 20PSIA
Vista 128BPE/FB/FBPE	Vista 21IP/IPSIA
Vista 128FBP	Vista 32FB
Vista 128SIA	First Alert FA130
Vista 15	First Alert FA148
Vista 15CN/P/PCN	First Alert FA168
Vista 15PSIA	Safewatch Pro 3000

DSC

Basic Signal only

PC1555
Alexor
Impassa
Neo

Full Support

PC1616
PC1832
PC1864



Basic Signal only

Nx 4v1
Nx 6v1
Nx 8v1
Nx 8E

Full Support*

Nx 4v2
Nx 6v2
Nx 8v2

**Upload/Download not supported*

TECHNICAL SPECIFICATIONS

RADIO:

- WiFi
802.11bg(mixed mode)

POWER:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

ENVIRONMENTAL:

- Temperature Range
- 30° to +70° C
(- 22° to +158° F)
- Humidity
0 to 95% non-condensing

PHYSICAL:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches

SECURITY PROTOCOLS SUPPORTED:

- WPA
- WPAII
- WEP

